

屋内照明器具特性	
品番 (品名)	NNN6 1 5 1 3 WK
光源	LDA7 L - G/ K6 ×1 810.0 lm
管理番号	K0178355 (0) DB 1
B Z 分類	BZ3

器具効率		70 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01)																
保守率		良 中 否	0.67	0.6	44	36	31	28	43	36	31	28	41	35	31	28	40	34	31	28	26
			0.63	0.8	51	44	39	36	50	44	39	36	48	43	39	36	47	42	38	35	34
			0.56	1.0	55	49	45	41	54	49	44	41	53	48	44	41	51	47	43	41	39
				1.25	59	54	50	46	58	53	49	46	56	52	49	46	55	51	48	46	44
下方投影面積 等価発光面積		cm ² cm ²		1.5	62	57	53	50	61	56	53	50	59	55	52	49	57	54	51	49	47
				2.0	65	61	58	55	64	60	57	55	62	59	56	54	61	58	56	54	52
				2.5	67	64	61	58	66	63	60	58	64	62	59	57	63	60	58	57	55
				3.0	69	66	63	61	68	65	62	60	66	63	61	60	64	62	60	59	57
H m	1.27 H m	1.27 H m		4.0	70	68	66	64	69	67	65	64	68	66	64	63	66	64	63	62	60
				5.0	71	69	68	66	70	69	67	66	69	67	66	65	67	66	65	64	62
				7.0	72	71	70	69	72	70	69	68	70	69	68	67	68	67	66	66	64
				10.0	73	72	71	70	72	72	71	70	71	70	69	69	69	69	68	67	65

