

屋内照明器具特性	
品番 (品名)	NNN6 1 5 1 4 WZ
光源	LDA13 L - G / Z100 E / S / W ×1 1520.0 l m
管理番号	K0158639 (0) DB 1
B Z 分類	BZ5 / 0.7 / BZ4

器具効率		59 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01)																Z C M
保守率		良 中 否	0.67	0.6	34	27	22	19	33	26	22	19	32	26	22	19	30	25	22	19	18
			0.63	0.8	40	34	29	26	39	33	29	26	38	32	29	26	36	32	28	26	24
			0.56	1.0	44	38	34	31	43	38	34	31	42	37	33	30	40	36	33	30	29
				1.25	48	42	38	35	47	42	38	35	45	41	38	35	44	40	37	35	33
下方投影面積		c m ²		1.5	50	45	42	39	49	45	41	38	47	44	41	38	46	43	40	38	36
			等価発光面積	c m ²	2.0	53	49	46	43	52	49	46	43	51	48	45	43	49	47	44	42
取付 高さ	器具間隔最大限			2.5	55	52	49	47	54	51	49	46	53	50	48	46	51	49	47	45	44
	横方向 (A) 縦方向 (B)			3.0	57	54	51	49	56	53	51	49	54	52	50	48	53	51	49	47	46
H m	1.36 H m	1.36 H m		4.0	58	56	54	52	58	55	54	52	56	54	53	51	54	53	52	50	49
				5.0	59	58	56	54	59	57	55	54	57	56	54	53	56	54	53	52	51
				7.0	61	59	58	57	60	58	57	56	58	57	56	55	57	56	55	54	53
				10.0	61	60	59	59	61	60	59	58	59	58	58	57	58	57	57	56	54

