

屋内照明器具特性	
品番 (品名)	NNN6 1 5 1 4 WZ
光源	LDA7 L - G / D / S / K6 ×1 810.0 lm
管理番号	K0167255 (0) DB 1
B Z 分類	BZ3

器具効率		72 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) ZCM																
保守率		良 中 否	0.67	0.6	46	38	33	29	45	37	33	29	43	37	32	29	42	36	32	29	28
			0.63	0.8	53	46	41	38	52	46	41	38	50	45	40	37	49	44	40	37	36
			0.56	1.0	58	51	47	43	57	51	47	43	55	50	46	43	53	49	45	43	41
				1.25	62	56	52	49	61	56	52	48	59	54	51	48	57	53	50	48	46
下方投影面積 等価発光面積		cm ² cm ²		1.5	64	59	55	52	63	59	55	52	62	58	54	52	60	56	54	51	50
				2.0	68	64	60	58	67	63	60	57	65	62	59	57	63	60	58	56	55
取付 高さ	器具間隔最大限			2.5	70	66	64	61	69	66	63	61	67	64	62	60	65	63	61	59	58
	横方向 (A) 縦方向 (B)			3.0	71	68	66	64	70	68	65	63	69	66	64	62	67	65	63	62	60
H m	1.23 H m 1.23 H m			4.0	73	71	69	67	72	70	68	66	70	69	67	65	69	67	66	64	63
				5.0	74	72	71	69	73	71	70	68	71	70	69	67	70	68	67	66	64
				7.0	75	74	73	71	74	73	72	71	73	72	71	70	71	70	69	68	66
				10.0	76	75	74	73	75	74	74	73	74	73	72	71	72	71	71	70	68

