

屋内照明器具特性	
品番 (品名)	NNN6 1 5 1 5 WK
光源	LDA7 L - H - E17 / S / 6 ×1 760.0 lm
管理番号	K0184263 (1) DB 1
B Z 分類	BZ5 / 1.1 / BZ4

器具効率		73 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) Z CM																
保守率		良 中 否	0.67	0.6	41	32	27	23	40	32	27	23	39	31	26	23	37	31	26	23	21
			0.63	0.8	49	41	35	31	48	40	35	31	46	39	34	31	44	38	34	31	29
			1.0	54	46	41	37	53	46	41	37	51	45	40	36	49	44	39	36	35	
			0.56	1.25	59	52	47	43	57	51	46	42	55	50	45	42	53	49	45	42	40
下方投影面積 等価発光面積		cm ² cm ²	1.5	62	55	51	47	61	55	50	47	58	53	49	46	56	52	49	46	44	
			2.0	66	61	56	53	65	60	56	53	62	58	55	52	60	57	54	52	50	
			2.5	68	64	60	57	67	63	60	57	65	62	59	56	63	60	58	55	54	
			3.0	70	66	63	60	69	66	63	60	67	64	61	59	65	62	60	58	56	
取付 高さ	器具間隔最大限		4.0	72	69	67	64	71	69	66	64	69	67	65	63	67	65	64	62	60	
	横方向 (A)		縦方向 (B)		5.0	74	71	69	67	73	70	68	66	71	69	67	65	69	67	66	64
	H m		1.41 H m		1.41 H m		7.0	75	73	72	70	74	73	71	70	72	71	70	68	71	
							10.0	76	75	74	73	75	74	73	72	74	73	72	71	72	

