

屋内照明器具特性	
品番 (品名)	NNN6 1 5 1 5 WK
光源	LDA6 L - H - E17 ×1 440.0 lm
管理番号	K0137751 (2) DB 1
BZ分類	BZ5 / 0.7 / BZ4

器具効率		80 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) ZCM																
保守率		良 中 否	0.67	0.6	46	36	30	26	45	36	30	26	43	35	29	26	41	34	29	25	24
			0.63	0.8	54	45	39	35	53	45	39	35	51	44	38	34	49	43	38	34	33
			0.56	1.0	60	52	46	41	59	51	45	41	56	50	45	41	54	48	44	41	39
				1.25	65	57	52	47	63	57	51	47	61	55	51	47	59	54	50	47	45
下方投影面積 等価発光面積		cm ² cm ²		1.5	68	61	56	52	67	61	56	52	64	59	55	51	62	58	54	51	49
				2.0	72	67	62	59	71	66	62	58	69	64	61	58	67	63	60	57	55
				2.5	75	70	66	63	74	70	66	63	72	68	65	62	69	66	64	61	59
				3.0	77	73	69	66	76	72	69	66	73	70	68	65	71	69	66	64	62
H _m	1.34 H _m	1.34 H _m		4.0	79	76	73	71	78	75	73	70	76	73	71	69	74	72	70	68	66
				5.0	81	78	76	74	80	77	75	73	77	75	73	72	75	74	72	71	69
				7.0	82	80	79	77	81	79	78	76	79	78	76	75	77	76	75	74	71
				10.0	83	82	81	80	82	81	80	79	80	79	78	77	79	78	77	76	74

