

屋内照明器具特性	
品番 (品名)	NNN6 1 5 1 5 WK
光源	LDA7 L - G - E17 / K60 E / S / W/ 2 × 1 760.0 lm
管理番号	K0157872 (0) DB 1
B Z 分類	BZ5

器具効率		69 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) Z CM																
保守率		良 中 否	0.67	0.6	38	29	24	20	37	29	23	20	35	28	23	20	34	27	23	19	18
			0.63	0.8	45	37	32	28	44	37	31	27	42	36	31	27	41	35	30	27	26
			0.56	1.0	50	43	37	33	49	42	37	33	47	41	36	33	45	40	36	33	31
				1.25	55	48	43	39	54	47	43	39	52	46	42	38	50	45	41	38	36
下方投影面積 等価発光面積		cm ²		1.5	58	52	47	43	57	51	46	43	55	50	46	42	53	48	45	42	40
				2.0	62	57	53	49	61	56	52	49	59	55	51	48	57	53	50	48	46
				2.5	64	60	56	53	63	59	56	53	61	58	55	52	59	56	54	52	50
				3.0	66	62	59	56	65	62	59	56	63	60	57	55	61	59	56	54	53
H m	1.59 H m	1.59 H m		4.0	68	65	63	60	67	65	62	60	65	63	61	59	63	62	60	58	56
				5.0	70	67	65	63	69	66	64	62	67	65	63	61	65	63	62	60	59
				7.0	71	69	68	66	70	69	67	66	68	67	66	64	67	65	64	63	61
				10.0	72	71	70	69	71	70	69	68	70	69	68	67	68	67	66	65	63

