

屋内照明器具特性	
品番 (品名)	NNN6 1 5 1 6 WK
光源	LDA4 L - H - E17 / S / 4 ×1 440.0 lm
管理番号	K0184834 (1) DB 1
BZ分類	BZ5 / 0.7 / BZ4

器具効率		71 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01)																Z C M
保守率		良 中 否	0.67	0.6	41	33	27	24	40	32	27	24	39	32	27	24	37	31	27	23	22
			0.63	0.8	49	41	36	32	48	41	36	32	46	40	35	32	45	39	35	32	30
			0.56	1.0	54	47	42	38	53	46	42	38	51	45	41	38	49	44	40	37	36
				1.25	58	52	47	44	57	51	47	43	55	50	46	43	53	49	46	43	41
下方投影面積		cm ²		1.5	61	56	51	48	60	55	51	47	58	54	50	47	56	52	49	47	45
			等価発光面積	cm ²	2.0	65	60	57	53	64	60	56	53	62	58	55	53	60	57	54	52
取付 高さ	器具間隔最大限			2.5	67	63	60	57	66	63	60	57	64	61	59	56	63	60	58	56	54
	横方向 (A)		縦方向 (B)	3.0	69	66	63	60	68	65	62	60	66	63	61	59	64	62	60	58	56
H m	1.47 H m		1.47 H m	4.0	71	68	66	64	70	68	65	63	68	66	64	62	66	65	63	62	60
				5.0	72	70	68	66	71	69	67	66	69	68	66	65	68	66	65	64	62
				7.0	74	72	70	69	73	71	70	68	71	70	68	67	69	68	67	66	64
				10.0	75	73	72	71	74	73	72	71	72	71	70	69	70	70	69	68	66

