

屋内照明器具特性	
品番 (品名)	NNN6 1 5 1 7 WK
光源	LDG4 L - G / 70 / W ×1 430.0 l m
管理番号	K0158877 (0) DB 1
BZ分類	BZ5 / 1.4 / BZ4

器具効率		73 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01)																Z C M
保守率		良 中 否	0.67	0.6	41	32	26	22	40	32	26	22	38	31	26	22	37	30	25	22	21
			0.63	0.8	49	40	35	30	48	40	34	30	46	39	34	30	44	38	33	30	28
			0.56	1.0	54	46	40	36	53	45	40	36	50	44	39	36	48	43	39	36	34
				1.25	58	51	46	42	57	51	46	42	55	49	45	41	53	48	44	41	39
下方投影面積		cm ²		1.5	61	55	50	46	60	54	50	46	58	53	49	46	56	52	48	45	43
			等価発光面積	cm ²	2.0	65	60	56	52	64	59	55	52	62	58	54	52	60	57	54	51
取付 高さ	器具間隔最大限			2.5	68	64	60	57	67	63	59	56	65	61	58	56	63	60	57	55	53
	横方向 (A) 縦方向 (B)			3.0	70	66	63	60	69	65	62	59	67	63	61	58	65	62	60	58	56
H m	1.44 H m	1.44 H m		4.0	72	69	66	64	71	68	66	63	69	66	64	62	67	65	63	61	60
				5.0	73	71	69	66	72	70	68	66	70	68	67	65	68	67	65	64	62
				7.0	75	73	71	70	74	72	71	69	72	71	69	68	70	69	68	67	65
				10.0	76	75	73	72	75	74	73	72	73	72	71	70	71	71	70	69	67

