

屋内照明器具特性	
品番 (品名)	NNN6 1 5 1 7 WK
光源	LDG4 L - G / 95 / W ×1 430.0 l m
管理番号	K0158875 (0) DB 1
B Z 分類	BZ5

器具効率		72 % 上方光束 1 % 下方光束 71 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) Z C M																
保守率		良 中 否	0.67	0.6	39	30	24	20	38	30	24	20	36	29	24	20	35	28	23	20	18
			0.63	0.8	46	38	32	28	45	37	32	27	43	36	31	27	41	35	31	27	25
			0.56	1.0	51	43	37	33	50	42	37	33	48	41	36	32	46	40	36	32	30
			1.25	56	48	43	38	54	47	42	38	52	46	41	38	50	45	41	37	36	
下方投影面積 等価発光面積		cm ²	1.5	59	52	47	42	57	51	46	42	55	50	45	42	53	48	44	41	39	
			2.0	63	57	52	48	61	56	52	48	59	55	51	47	57	53	50	47	45	
取付 高さ	器具間隔最大限		2.5	65	60	56	53	64	60	56	52	62	58	54	52	60	56	53	51	49	
	横方向 (A) 縦方向 (B)		3.0	67	63	59	56	66	62	58	55	64	60	57	55	61	59	56	54	52	
H m	1.43 H m	1.43 H m	4.0	70	66	63	60	68	65	62	60	66	63	61	59	64	62	60	58	56	
			5.0	71	68	65	63	70	67	65	62	68	65	63	61	66	64	62	60	58	
			7.0	73	71	68	67	72	70	68	66	70	68	66	65	68	66	65	63	61	
			10.0	74	72	71	69	73	72	70	69	71	70	69	67	69	68	67	66	64	

