

屋内照明器具特性	
品番 (品名)	L G B 8 1 7 0 3
光源	LED5000_70_453 ×1 453.0 lm
管理番号	K0152279 (0) DB 1
B Z 分類	B Z 6

器具効率		1 0 0 %	反射率	天井	8 0 %					7 0 %					5 0 %					3 0 %					0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %				
				床	1 0 %					1 0 %					1 0 %					1 0 %					0 %
上方光束		2 3 %	室指数	照明率 (X 0 . 0 1)																				Z C M	
下方光束		7 7 %																							
保守率		良 中 否	0 . 6 3	0 . 6	5 0	3 7	2 9	2 4	4 7	3 6	2 8	2 3	4 3	3 3	2 6	2 2	3 8	3 0	2 4	2 0	1 7				
			0 . 6	0 . 8	5 9	4 7	3 9	3 2	5 6	4 5	3 7	3 1	5 1	4 1	3 5	3 0	4 5	3 8	3 2	2 8	2 3				
			0 . 5 6	1 . 0	6 5	5 4	4 5	3 9	6 2	5 1	4 4	3 8	5 6	4 7	4 1	3 5	5 0	4 3	3 8	3 3	2 8				
				1 . 2 5	7 1	6 0	5 2	4 6	6 8	5 8	5 0	4 4	6 1	5 3	4 7	4 2	5 5	4 8	4 3	3 9	3 3				
下方投影面積		c m ²	1 . 5	7 5	6 5	5 7	5 1	7 2	6 2	5 5	5 0	6 5	5 7	5 1	4 6	5 8	5 2	4 7	4 3	3 7					
等価発光面積			c m ²	2 . 0	8 1	7 2	6 5	5 9	7 7	6 9	6 3	5 7	7 0	6 4	5 8	5 4	6 3	5 8	5 4	5 0	4 3				
取付 高さ	器具間隔最大限		2 . 5	8 5	7 7	7 1	6 5	8 1	7 4	6 8	6 3	7 3	6 8	6 3	5 9	6 7	6 2	5 8	5 5	4 7					
	横方向 (A)		縦方向 (B)	3 . 0	8 7	8 0	7 5	6 9	8 3	7 7	7 2	6 7	7 6	7 1	6 6	6 3	6 9	6 5	6 1	5 8	5 1				
H m	1 . 4 1 H m	1 . 3 5 H m	4 . 0	9 1	8 5	8 0	7 6	8 7	8 2	7 7	7 3	7 9	7 5	7 1	6 8	7 2	6 9	6 6	6 3	5 5					
			5 . 0	9 3	8 8	8 4	8 0	8 9	8 5	8 1	7 7	8 1	7 8	7 5	7 2	7 4	7 2	6 9	6 7	5 8					
			7 . 0	9 5	9 2	8 8	8 5	9 1	8 8	8 5	8 2	8 4	8 1	7 9	7 6	7 7	7 5	7 3	7 1	6 2					
			1 0 . 0	9 7	9 5	9 2	9 0	9 4	9 1	8 9	8 6	8 6	8 4	8 2	8 0	7 9	7 8	7 6	7 4	6 6					

