

屋内照明器具特性	
品番 (品名)	XLJ 440 NENK
光源	LED5000_85_3830 ×1 3830.0 lm
管理番号	K0141079 (5) DB1
BZ分類	BZ5

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %				
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
				床	10 %				10 %				10 %				10 %				0 %				
上方光束		6 %	室指数	照明率 (X0.01)																			Z	C	M
下方光束		94 %																							
保守率		良 中 否	0.83	0.6	55	42	34	29	53	42	34	29	50	40	33	28	47	38	32	28	25				
			0.81	0.8	64	53	45	39	63	52	44	38	59	50	43	38	56	48	42	37	34				
			0.77	1.0	71	60	52	46	69	59	51	45	65	56	50	45	62	54	48	44	41				
				1.25	77	67	59	53	75	65	58	53	71	63	56	51	67	60	55	50	47				
下方投影面積		cm ²	1.5	81	72	64	59	79	70	63	58	75	67	61	57	71	65	60	55	52					
			2.0	87	79	72	67	84	77	71	66	80	74	69	64	76	71	67	63	59					
取付 高さ	器具間隔最大限		2.5	90	83	77	73	88	82	76	72	84	78	74	70	80	75	71	68	64					
	横方向 (A)		縦方向 (B)		3.0	93	87	81	77	90	85	80	76	86	82	77	74	82	78	75	72	68			
1.5m	1.97 m	2.09 m	4.0	96	91	87	83	94	89	85	82	90	86	82	79	86	83	80	77	73					
2	2.6	2.65	5.0	98	94	90	87	96	92	89	85	92	88	86	83	88	85	83	81	76					
2.5	3.24	3.22	7.0	100	97	94	91	98	95	93	90	94	92	89	87	90	88	87	85	80					
3	3.86	3.82	10.0	102	100	98	95	100	98	96	94	96	94	93	91	92	91	90	88	84					

