

屋内照明器具特性

品番 (品名)	LGB52643	
光源	LED2700_70_1410 x1 1410.0 lm	
管理番号	K0147586(0)DB1	
BZ分類	BZ6/0.7/BZ5/3.5/BZ6/4.5/BZ5 /6.0/BZ6	

器具効率	100%	天井	80%				70%				50%				30%				0%		
	上方光束 11%		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
下方光束	89%	床		10%				10%				10%				10%				0%	
室指数	照明率 (X0.01)																				ZCM
保守率	良	0.63	0.6	53	41	33	27	52	40	32	27	48	38	31	26	45	36	30	26	23	
	中	0.6	0.8	63	51	43	37	61	50	42	36	57	47	40	35	53	45	39	34	31	
	否	0.56	1.0	69	58	50	44	67	56	49	43	62	54	47	42	58	51	45	41	37	
			1.25	75	65	57	51	72	63	56	50	68	60	53	48	63	57	51	47	43	
下方投影面積	cm ²		1.5	79	69	62	56	76	68	61	55	72	64	58	53	67	61	56	52	47	
等価発光面積	cm ²		2.0	85	76	70	64	82	74	68	63	77	71	65	61	72	67	63	59	54	
取付高さ	器具間隔最大限		2.5	88	81	75	70	86	79	73	69	80	75	70	66	76	71	67	64	59	
	横方向 (A)	縦方向 (B)	3.0	91	84	79	74	88	82	77	73	83	78	74	70	78	74	71	67	63	
H _m	1.29H _m	1.29H _m	4.0	94	89	84	80	91	87	82	79	86	82	79	76	82	78	75	73	67	
			5.0	96	92	88	84	94	90	86	82	89	85	82	79	84	81	78	76	71	
			7.0	99	95	92	89	96	93	90	87	91	89	86	84	86	84	82	80	75	
			10.0	101	98	96	93	98	96	93	91	93	91	89	88	89	87	85	84	78	

