

屋内照明器具特性	
品番 (品名)	S F 0 5 5 B
光源	LED2700_70_740 ×1 740.0 l m
管理番号	K0148410 (0) DB 1
B Z 分類	BZ5

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
上方光束	10 %	床	10 %				10 %				10 %				10 %				0 %	
下方光束	90 %	室指数	照明率 (X0.01)																ZCM	
保守率	良	0.67	0.6	5.5	4.3	3.5	3.0	5.3	4.2	3.5	2.9	5.0	4.0	3.4	2.9	4.7	3.8	3.2	2.8	2.6
	中	0.63	0.8	6.5	5.3	4.5	4.0	6.3	5.2	4.5	3.9	5.9	5.0	4.3	3.8	5.5	4.7	4.2	3.7	3.4
	否	0.56	1.0	7.1	6.0	5.2	4.7	6.9	5.9	5.2	4.6	6.5	5.6	5.0	4.5	6.1	5.4	4.8	4.4	4.0
			1.25	7.7	6.7	6.0	5.4	7.4	6.5	5.8	5.3	7.0	6.2	5.6	5.2	6.6	5.9	5.4	5.0	4.6
下方投影面積		cm ²	1.5	8.1	7.2	6.5	5.9	7.8	7.0	6.3	5.8	7.4	6.7	6.1	5.7	7.0	6.4	5.9	5.5	5.1
等価発光面積		cm ²	2.0	8.6	7.9	7.2	6.7	8.4	7.7	7.1	6.6	7.9	7.3	6.8	6.4	7.5	7.0	6.6	6.2	5.8
取付高さ	器具間隔最大限		2.5	9.0	8.3	7.7	7.3	8.7	8.1	7.6	7.1	8.2	7.7	7.3	6.9	7.8	7.4	7.0	6.7	6.2
	横方向 (A)	縦方向 (B)	3.0	9.2	8.6	8.1	7.7	9.0	8.4	8.0	7.5	8.5	8.0	7.6	7.3	8.0	7.7	7.3	7.0	6.6
1.5m	1.87 m	1.95 m	4.0	9.5	9.0	8.6	8.2	9.3	8.8	8.4	8.1	8.8	8.4	8.1	7.8	8.4	8.1	7.8	7.5	7.0
2	2.48	2.56	5.0	9.7	9.3	8.9	8.6	9.5	9.1	8.8	8.5	9.0	8.7	8.4	8.1	8.6	8.3	8.1	7.9	7.3
2.5	3.11	3.18	7.0	10.0	9.6	9.4	9.1	9.7	9.4	9.2	8.9	9.2	9.0	8.8	8.6	8.8	8.6	8.4	8.3	7.7
3	3.73	3.81	10.0	10.1	9.9	9.7	9.5	9.9	9.7	9.5	9.3	9.4	9.3	9.1	8.9	9.0	8.9	8.7	8.6	8.0

