

屋内照明器具特性	
品番 (品名)	S F 0 7 5 W
光源	LED2700_70_255 ×1 255.0 l m
管理番号	K0158541 ( 0 ) DR 1
B Z 分類	BZ10

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %	
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
上方光束	100 %	反射率	壁	10 %				10 %				10 %				10 %				0 %
下方光束	0 %		床	10 %				10 %				10 %				10 %				0 %
		室指数	照明率 ( X 0 . 0 1 )																Z C M	
保守率	良 0.67	0.6	43	33	26	21	37	28	23	19	25	19	16	13	14	11	9	8	0	
	中 0.63	0.8	51	41	34	29	43	35	29	25	29	24	21	18	17	14	12	10	0	
	否 0.56	1.0	56	47	40	35	48	40	35	31	33	28	24	22	18	16	14	13	0	
下方投影面積	c m <sup>2</sup>	1.25	61	53	46	41	52	45	40	36	36	31	28	25	20	18	16	15	0	
		1.5	65	57	51	46	55	49	44	40	38	34	31	28	22	20	18	17	0	
等価発光面積	c m <sup>2</sup>	2.0	70	63	58	54	60	54	50	47	41	38	35	33	23	22	20	19	0	
		2.5	73	67	62	59	62	58	54	51	43	40	38	36	25	23	22	21	0	
取付高さ	器具間隔最大限		3.0	75	70	66	62	64	60	57	54	44	42	40	38	25	24	23	0	
H m	横方向 ( A )	縦方向 ( B )	4.0	77	74	70	67	67	64	61	58	46	44	42	41	27	26	25	0	
	0.20 H m	0.20 H m	5.0	79	76	73	70	68	66	63	61	47	46	44	43	27	27	26	0	
			7.0	81	79	77	75	70	68	66	65	48	47	46	45	28	28	27	0	
			10.0	83	81	79	78	71	70	69	67	49	49	48	47	29	28	28	0	

