

| 屋内照明器具特性 |                              |
|----------|------------------------------|
| 品番 (品名)  | XL X8 6 0 DE WJ              |
| 光源       | LED4000_85_5960 ×1 5960.0 lm |
| 管理番号     | K0130919 ( * ) DB 1          |
| BZ分類     | BZ5                          |

| 器具効率   |         | 100 %           | 反射率  | 天井            | 80 % |    |    |     | 70 % |    |    |    | 50 % |    |    |    | 30 % |    |    |    | 0 % |   |   |
|--------|---------|-----------------|------|---------------|------|----|----|-----|------|----|----|----|------|----|----|----|------|----|----|----|-----|---|---|
|        |         |                 |      | 壁             | 70   | 50 | 30 | 10  | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 0 % |   |   |
|        |         |                 |      | 床             | 10 % |    |    |     | 10 % |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 0 % |   |   |
| 上方光束   |         | 4 %             | 室指数  | 照明率 ( X0.01 ) |      |    |    |     |      |    |    |    |      |    |    |    |      |    |    |    | Z   | C | M |
| 下方光束   |         | 96 %            |      |               |      |    |    |     |      |    |    |    |      |    |    |    |      |    |    |    |     |   |   |
| 保守率    |         | 良<br>中<br>否     | 0.83 | 0.6           | 55   | 42 | 34 | 29  | 53   | 42 | 34 | 29 | 51   | 40 | 33 | 28 | 48   | 39 | 33 | 28 | 26  |   |   |
|        |         |                 | 0.81 | 0.8           | 65   | 53 | 45 | 39  | 63   | 52 | 44 | 38 | 60   | 50 | 43 | 38 | 57   | 48 | 42 | 37 | 35  |   |   |
|        |         |                 | 0.77 | 1.0           | 71   | 60 | 52 | 46  | 69   | 59 | 51 | 46 | 66   | 57 | 50 | 45 | 62   | 55 | 49 | 44 | 42  |   |   |
|        |         |                 |      | 1.25          | 77   | 67 | 59 | 53  | 75   | 66 | 58 | 53 | 71   | 63 | 57 | 52 | 68   | 61 | 56 | 51 | 48  |   |   |
| 下方投影面積 |         | cm <sup>2</sup> | 1.5  | 81            | 72   | 65 | 59 | 79  | 70   | 64 | 58 | 75 | 68   | 62 | 57 | 72 | 66   | 60 | 56 | 53 |     |   |   |
| 等価発光面積 |         | cm <sup>2</sup> | 2.0  | 87            | 79   | 72 | 67 | 85  | 77   | 71 | 66 | 81 | 75   | 69 | 65 | 77 | 72   | 68 | 64 | 60 |     |   |   |
| 取付高さ   | 器具間隔最大限 |                 | 2.5  | 90            | 84   | 78 | 73 | 88  | 82   | 77 | 72 | 85 | 79   | 74 | 70 | 81 | 76   | 72 | 69 | 66 |     |   |   |
|        | 横方向 (A) | 縦方向 (B)         | 3.0  | 93            | 87   | 82 | 77 | 91  | 85   | 80 | 76 | 87 | 82   | 78 | 75 | 84 | 80   | 76 | 73 | 69 |     |   |   |
| 1.5m   | 2.08 m  | 2.88 m          | 4.0  | 96            | 91   | 87 | 83 | 94  | 90   | 86 | 82 | 91 | 87   | 83 | 80 | 87 | 84   | 81 | 78 | 75 |     |   |   |
| 2      | 2.71    | 3.3             | 5.0  | 98            | 94   | 90 | 87 | 96  | 93   | 89 | 86 | 93 | 89   | 86 | 84 | 89 | 87   | 84 | 82 | 78 |     |   |   |
| 2.5    | 3.34    | 3.79            | 7.0  | 101           | 97   | 95 | 92 | 99  | 96   | 93 | 91 | 95 | 93   | 90 | 88 | 92 | 90   | 88 | 86 | 82 |     |   |   |
| 3      | 3.97    | 4.32            | 10.0 | 102           | 100  | 98 | 96 | 101 | 99   | 96 | 95 | 97 | 95   | 94 | 92 | 94 | 92   | 91 | 90 | 86 |     |   |   |

