

| 屋内照明器具特性 |                              |
|----------|------------------------------|
| 品番 (品名)  | NNLK81517+NNL8600ENJ         |
| 光源       | LED5000_85_6270 ×1 6270.0 lm |
| 管理番号     | K0130921 ( * ) DB 1          |
| BZ分類     | BZ5                          |

| 器具効率   |  |           | 100 %           |           | 反射率             | 天井  | 80 %          |     |    |     | 70 % |    |    |     | 50 % |    |    |    | 30 % |    |    |    | 0 % |
|--------|--|-----------|-----------------|-----------|-----------------|-----|---------------|-----|----|-----|------|----|----|-----|------|----|----|----|------|----|----|----|-----|
|        |  |           |                 |           |                 | 壁   | 70            | 50  | 30 | 10  | 70   | 50 | 30 | 10  | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 0 % |
|        |  |           |                 |           |                 | 床   | 10 %          |     |    |     | 10 % |    |    |     | 10 % |    |    |    | 10 % |    |    |    | 0 % |
|        |  |           |                 |           |                 | 室指数 | 照明率 ( X0.01 ) |     |    |     |      |    |    |     |      |    |    |    |      |    |    |    |     |
| 保守率    |  |           | 良<br>中<br>否     | 0.81      | 0.6             | 56  | 44            | 36  | 31 | 55  | 43   | 36 | 30 | 52  | 42   | 35 | 30 | 50 | 41   | 35 | 30 | 28 |     |
|        |  |           |                 | 0.77      | 0.8             | 66  | 55            | 47  | 41 | 65  | 54   | 46 | 41 | 62  | 52   | 46 | 41 | 59 | 51   | 45 | 40 | 38 |     |
|        |  |           |                 | 0.68      | 1.0             | 73  | 62            | 54  | 48 | 71  | 61   | 54 | 48 | 68  | 60   | 53 | 48 | 66 | 58   | 52 | 48 | 45 |     |
|        |  |           |                 |           | 1.25            | 79  | 69            | 62  | 56 | 77  | 68   | 61 | 56 | 74  | 66   | 60 | 55 | 71 | 65   | 59 | 55 | 53 |     |
| 下方投影面積 |  |           | cm <sup>2</sup> | 1.5       | 83              | 74  | 67            | 62  | 81 | 73  | 67   | 61 | 78 | 71  | 66   | 61 | 76 | 69 | 65   | 60 | 58 |    |     |
|        |  |           |                 | 等価発光面積    | cm <sup>2</sup> | 2.0 | 89            | 81  | 75 | 70  | 87   | 80 | 75 | 70  | 84   | 78 | 73 | 69 | 81   | 76 | 72 | 68 | 66  |
| 取付高さ   |  | 器具間隔最大限   |                 |           | 2.5             | 92  | 86            | 81  | 76 | 91  | 85   | 80 | 76 | 88  | 83   | 79 | 75 | 85 | 81   | 77 | 74 | 71 |     |
|        |  | 横方向 ( A ) |                 | 縦方向 ( B ) | 3.0             | 95  | 89            | 85  | 81 | 93  | 88   | 84 | 80 | 90  | 86   | 82 | 79 | 88 | 84   | 81 | 78 | 75 |     |
| 1.5m   |  | 2.06 m    | 2.87 m          |           | 4.0             | 98  | 94            | 90  | 87 | 97  | 93   | 89 | 86 | 94  | 90   | 87 | 85 | 91 | 88   | 86 | 83 | 81 |     |
| 2      |  | 2.69      | 3.3             |           | 5.0             | 100 | 97            | 93  | 90 | 99  | 95   | 92 | 90 | 96  | 93   | 91 | 88 | 93 | 91   | 89 | 87 | 84 |     |
| 2.5    |  | 3.31      | 3.79            |           | 7.0             | 102 | 100           | 97  | 95 | 101 | 98   | 96 | 94 | 98  | 96   | 94 | 92 | 96 | 94   | 92 | 91 | 88 |     |
| 3      |  | 3.94      | 4.33            |           | 10.0            | 104 | 102           | 100 | 99 | 103 | 101  | 99 | 98 | 100 | 99   | 97 | 96 | 98 | 96   | 95 | 94 | 91 |     |

