

屋内照明器具特性

品番 (品名)	LGBC81023														
光源	LED2700_70_1440 x1 1440.0 lm														
管理番号	K0147589(0)DB1														
BZ分類	BZ6/0.7/BZ5/3.5/BZ6														

器具効率	100%	天井	80%				70%				50%				30%				0%		
	上方光束		13%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		87%		床	10%				10%				10%				10%			
室指数		照明率 (X0.01) ZCM																			
保守率	良	0.63	0.6	53	40	32	27	51	39	32	26	47	37	31	26	44	35	29	25	22	
	中	0.6	0.8	62	50	42	36	60	49	41	36	56	46	40	34	52	44	38	33	30	
	否	0.56	1.0	69	57	49	43	66	56	48	42	61	53	46	41	57	50	44	39	36	
			1.25	74	64	56	50	72	62	55	49	67	59	52	47	62	55	50	46	42	
下方投影面積	cm ²		1.5	78	69	61	55	76	67	60	54	71	63	57	52	66	60	55	50	46	
	等価発光面積		cm ²	2.0	84	76	69	63	81	74	67	62	76	70	64	60	71	66	61	57	53
取付高さ	器具間隔最大限		2.5	88	80	74	69	85	78	73	68	79	74	69	65	74	70	66	62	57	
	横方向 (A)	縦方向 (B)	3.0	90	84	78	73	87	82	76	72	82	77	73	69	77	73	69	66	61	
Hm	1.29Hm	1.29Hm	4.0	94	88	84	79	91	86	82	78	85	81	78	74	80	77	74	71	66	
			5.0	96	91	87	83	93	89	85	82	87	84	81	78	82	80	77	75	69	
			7.0	98	95	91	88	95	92	89	87	90	87	85	83	85	83	81	79	73	
			10.0	100	97	95	93	97	95	93	91	92	90	88	87	87	86	84	83	76	

