

屋内照明器具特性

品番 (品名)	LGBC81043									
光源	LED2700_70_1410 x1 1410.0 lm									
管理番号	K0147588(0)DB1									
BZ分類	BZ6/0.7/BZ5/3.5/BZ6									

器具効率	100%	天井	80%				70%				50%				30%				0%		
	上方光束		9%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		91%		床	10%				10%				10%				10%			
室指数	照明率 (X0.01) ZCM																				
保守率	良	0.63	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6
	中	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6
	否	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56
	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56
下方投影面積	c m ²		1.25	75	64	57	50	73	63	55	50	68	60	53	48	64	57	52	47	43	
	等価発光面積	c m ²		1.5	79	69	62	56	77	68	61	55	72	64	58	53	68	61	56	52	48
取付高さ		器具間隔最大限		2.0	85	76	70	64	82	75	68	63	77	71	66	61	73	68	63	59	55
	H m	横方向 (A)	縦方向 (B)	2.5	88	81	75	70	86	79	73	68	81	75	71	66	77	72	68	64	60
1.29 H m		1.29 H m	3.0	91	84	79	74	88	82	77	73	84	79	74	70	79	75	71	68	63	
			4.0	94	89	84	80	92	87	83	79	87	83	79	76	83	79	76	73	68	
			5.0	96	92	88	84	94	90	86	83	89	86	83	80	85	82	79	77	72	
			7.0	99	95	92	89	96	93	90	87	92	89	87	84	88	85	83	81	76	
			10.0	101	98	96	93	98	96	94	92	94	92	90	88	90	88	86	85	80	

