

屋内照明器具特性	
品番 (品名)	XL X830 RHWJ
光源	LED4000_85_12280 ×1 12280.0 lm
管理番号	K0128266 (3) DB 1
BZ分類	BZ5

器具効率			100 %		反射率	天井	80 %				70 %				50 %				30 %				0 %			
						壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
						床	10 %				10 %				10 %				10 %				0 %			
上方光束			0 %		室指数	照明率 (X0.01)																			Z CM	
下方光束			100 %																							
保守率			良 中 否	0.81	0.6	56	43	35	30	54	43	35	30	52	42	35	30	50	41	34	30	28				
				0.77	0.8	66	54	46	40	64	53	46	40	62	52	45	40	59	51	44	40	38				
				0.68	1.0	73	62	54	48	71	61	53	48	68	59	53	47	65	58	52	47	45				
					1.25	79	69	61	56	77	68	61	55	74	66	60	55	71	64	59	54	52				
下方投影面積			cm ²	1.5	83	74	67	61	81	73	66	61	78	71	65	60	75	69	64	60	57					
				2.0	89	81	75	70	87	80	74	70	84	78	73	69	81	76	72	68	66					
等価発光面積			cm ²	2.5	93	86	81	76	91	85	80	76	88	83	78	75	85	81	77	74	71					
				3.0	95	89	85	80	93	88	84	80	91	86	82	79	88	84	81	78	75					
取付高さ		器具間隔最大限			4.0 <td>98</td> <td>94</td> <td>90</td> <td>87</td> <td>97</td> <td>93</td> <td>89</td> <td>86</td> <td>94</td> <td>91</td> <td>87</td> <td>85</td> <td>91</td> <td>88</td> <td>86</td> <td>83</td> <td>81</td>	98	94	90	87	97	93	89	86	94	91	87	85	91	88	86	83	81				
		横方向 (A)		縦方向 (B)	5.0	100	97	93	90	99	95	92	90	96	93	91	88	93	91	89	87	84				
1.5m		2.13 m		2.89 m	7.0	103	100	97	95	101	99	96	94	98	96	94	93	96	94	93	91	88				
2		2.77		3.32	10.0	104	102	100	99	103	101	99	98	100	99	97	96	98	97	95	94	91				
2.5		3.41		3.82																						
3		4.06		4.36																						

