

屋内照明器具特性	
品番 (品名)	XLX860VENJ
光源	LED5000_85_6200 ×1 6200.0lm
管理番号	K0130922 (5) DB1
BZ分類	BZ5

器具効率			100 %		反射率	天井	80 %				70 %				50 %				30 %				0 %
						壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
						床	10 %				10 %				10 %				10 %				0 %
						照明率 (X0.01) Z CM																	
保守率			良 中 否	0.81	0.6	56	43	35	29	54	42	35	29	52	41	34	29	50	40	34	29	27	
				0.77	0.8	66	54	46	40	64	53	45	40	61	51	45	39	59	50	44	39	37	
				0.68	1.0	72	61	53	47	71	60	53	47	68	59	52	47	65	57	51	46	44	
					1.25	78	68	60	55	77	67	60	54	73	65	59	54	70	64	58	53	51	
下方投影面積			cm ²	1.5	82	73	66	60	81	72	65	60	78	70	64	59	75	68	63	59	56		
				2.0	88	81	74	69	87	79	73	69	83	77	72	68	80	75	71	67	64		
等価発光面積			cm ²	2.5	92	85	80	75	90	84	79	74	87	82	77	73	84	80	76	73	70		
				3.0	95	89	84	79	93	88	83	79	90	85	81	78	87	83	80	77	74		
1.5m			2.09 m	2.88 m	4.0	98	93	89	86	96	92	88	85	93	90	87	84	91	88	85	82	80	
2			2.72	3.31	5.0	100	96	93	89	98	95	92	89	96	93	90	87	93	90	88	86	83	
2.5			3.35	3.8	7.0	102	99	97	94	101	98	96	93	98	96	94	92	96	94	92	90	87	
3			3.99	4.33	10.0	104	102	100	98	103	101	99	97	100	98	97	96	98	96	95	94	91	

