

屋内照明器具特性

品番 (品名)	NYY16906		
光源	NYY16906 x1 585.0 lm		
管理番号	K0126303 (1) DB1		
BZ分類	BZ1		

器具効率	100%	天井	80%				70%				50%				30%				0%
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	
上方光束	0%	反射率	10%				10%				10%				10%				0%
下方光束	100%		室指数	照明率 (X0.01)															
保守率	良 0.67	0.6	86	80	77	74	85	80	77	74	84	79	76	74	83	79	76	74	73
	中 0.63	0.8	92	87	84	81	91	86	83	81	90	86	83	81	88	85	82	80	79
	否 0.56	1.0	95	91	88	85	94	90	87	85	93	89	87	85	91	88	86	84	83
下方投影面積	cm ²	1.25	98	94	91	89	97	94	91	89	95	92	90	88	94	91	89	88	86
		1.5	100	96	94	92	99	96	93	91	97	94	92	91	95	93	91	90	89
等価発光面積	cm ²	2.0	102	99	97	95	101	98	96	95	99	97	95	94	97	96	94	93	91
		2.5	103	101	99	97	102	100	98	97	100	99	97	96	98	97	96	95	93
取付高さ	器具間隔最大限		3.0	104	102	100	99	103	101	100	98	101	100	98	97	99	98	97	96
	横方向 (A)	縦方向 (B)	4.0	105	104	102	101	104	103	101	100	102	101	100	99	100	99	98	98
Hm	0.61Hm	0.61Hm	5.0	106	105	103	102	105	104	103	102	103	102	101	100	101	100	99	99
			7.0	107	106	105	104	105	105	104	103	103	103	102	101	101	101	100	100
			10.0	107	106	106	105	106	105	105	104	104	103	103	102	102	101	101	98

