

屋内照明器具特性	
品番 (品名)	LGB81774
光源	LED3500_70_4530 ×1 4530.0 lm
管理番号	K0161533 (0) DR1
BZ分類	BZ8

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) ZCM																
保守率		良 中 否	0.63	0.6	45	33	25	19	41	30	23	18	34	25	19	15	27	20	16	12	7
			0.6	0.8	53	41	33	27	49	38	31	25	40	32	26	21	32	26	21	17	11
				1.0	59	48	39	33	54	44	36	31	45	37	31	26	36	30	25	21	13
			0.56	1.25	65	54	46	40	59	50	42	37	49	42	36	31	40	34	29	26	17
下方投影面積		cm ²		1.5	69	59	51	45	63	54	47	41	52	45	40	35	42	37	33	29	19
			等価発光面積	cm ²	2.0	75	66	59	53	68	61	54	49	57	51	46	42	46	42	38	34
取付 高さ	器具間隔最大限		2.5	78	70	64	58	72	65	59	54	60	55	50	46	49	45	41	38	26	
	横方向 (A) 縦方向 (B)			3.0	81	74	68	63	74	68	63	58	62	58	53	50	51	48	44	41	28
1.5m	2.44 m	2.16 m	4.0	84	78	73	69	78	73	68	64	66	62	58	55	54	51	48	46	32	
2	3.22	2.71	5.0	86	82	77	73	80	76	72	68	68	64	61	58	56	53	51	49	34	
2.5	4	3.29	7.0	89	85	82	78	83	79	76	73	70	67	65	62	58	56	54	52	37	
3	4.79	3.88	10.0	91	88	86	83	85	82	80	77	72	70	68	66	60	59	57	56	40	

