

屋内照明器具特性	
品番 (品名)	LGB85045
光源	LED5000_70_840 ×1 840.0 lm
管理番号	K0189642 (0) DR1
BZ分類	BZ8/3.5/BZ7/8.5/BZ8

器具効率		100 %	反射率	天井	80 %					70 %					50 %					30 %					0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
				床	10 %					10 %					10 %					10 %					0 %
				室指数	照明率 (X0.01)																				ZCM
保守率		良 中 否	0.63	0.6	45	33	25	20	41	30	23	18	34	25	19	15	27	21	16	12	7				
			0.6	0.8	54	42	33	27	49	38	31	25	40	32	26	21	33	26	21	18	11				
			0.56	1.0	60	48	40	33	54	44	37	31	45	37	31	26	36	30	25	22	14				
				1.25	65	54	46	40	60	50	43	37	49	42	36	31	40	34	30	26	17				
下方投影面積		cm ²		1.5	69	59	51	45	63	54	47	42	53	46	40	36	43	37	33	29	19				
			等価発光面積	cm ²	2.0	75	66	59	53	69	61	54	49	57	51	46	42	47	42	38	35	23			
取付 高さ	器具間隔最大限			2.5	78	71	64	59	72	65	59	54	60	55	50	46	49	45	42	39	26				
	横方向 (A) 縦方向 (B)			3.0	81	74	68	63	75	68	63	59	63	58	54	50	51	48	45	42	29				
1.5m	2.33 m	1.85 m	4.0	84	79	74	69	78	73	68	64	66	62	58	55	54	51	48	46	32					
2	3.09	2.45	5.0	87	82	77	73	80	76	72	68	68	64	61	58	56	53	51	49	34					
2.5	3.87	3.04	7.0	89	85	82	79	83	79	76	73	70	67	65	63	58	56	54	53	37					
3	4.64	3.65	10.0	91	88	86	83	85	82	80	77	72	70	68	66	60	59	57	56	40					

