

屋内照明器具特性	
品番 (品名)	L G W C 8 0 2 7 0
光源	L E D 2 7 0 0 _ 7 0 _ 4 9 2 × 1 4 9 2 . 0 l m
管理番号	K 0 1 6 0 2 5 7 (0) D R 1
B Z 分類	B Z 1 0

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %			
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
				床	10 %				10 %				10 %				10 %				0 %			
上方光束		50 %	室指数	照明率 (X0.01)																			Z	CM
下方光束		50 %																						
保守率		良 中 否	0.63	0.6	43	30	22	16	39	27	20	14	31	22	16	12	25	17	12	9	3			
			0.6	0.8	51	38	29	23	46	34	27	21	37	28	22	17	29	22	17	13	6			
			0.56	1.0	57	44	35	28	51	40	32	26	42	33	26	21	33	26	21	17	9			
				1.25	62	50	41	34	56	46	38	32	46	38	31	26	36	30	25	21	11			
下方投影面積		cm ²	1.5	66	55	47	40	60	50	43	36	49	41	35	30	39	33	28	24	14				
等価発光面積		cm ²	2.0	72	62	54	48	66	57	50	44	54	47	42	37	43	38	33	30	18				
取付 高さ	器具間隔最大限		2.5	76	67	60	54	69	62	55	49	57	51	46	41	46	41	37	34	21				
	横方向 (A)	縦方向 (B)	3.0	79	71	64	58	72	65	59	54	60	54	49	45	48	44	40	37	24				
H m	0.00 H m	0.00 H m	4.0	82	76	70	65	76	70	65	60	63	59	54	51	51	48	44	41	27				
			5.0	85	79	74	69	78	73	68	64	65	61	58	54	53	50	47	45	30				
			7.0	88	83	79	75	81	77	73	70	68	65	62	59	56	54	51	49	34				
			10.0	90	87	83	80	83	80	77	75	71	68	66	64	58	57	55	53	37				

