

| 屋内照明器具特性 |                            |
|----------|----------------------------|
| 品番 (品名)  | L G W8 0 2 7 1             |
| 光源       | LED2700_70_466 ×1 466.0 lm |
| 管理番号     | K0160258 ( 0 ) DR 1        |
| B Z 分類   | BZ10                       |

| 器具効率   |           | 100 %<br><br>上方光束<br>50 %<br>下方光束 | 反射率             | 天井   | 80 %              |    |    |    | 70 % |    |    |    | 50 % |    |    |    | 30 % |    |    |    | 0 % |
|--------|-----------|-----------------------------------|-----------------|------|-------------------|----|----|----|------|----|----|----|------|----|----|----|------|----|----|----|-----|
|        |           |                                   |                 | 壁    | 70                | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 0 % |
|        |           |                                   |                 | 床    | 10 %              |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 0 % |
|        |           |                                   |                 | 室指数  | 照明率 ( X0.01) Z CM |    |    |    |      |    |    |    |      |    |    |    |      |    |    |    |     |
| 保守率    |           | 良<br>中<br>否                       | 0.63            | 0.6  | 43                | 30 | 21 | 16 | 39   | 27 | 20 | 14 | 31   | 22 | 16 | 11 | 25   | 17 | 12 | 9  | 3   |
|        |           |                                   | 0.6             | 0.8  | 51                | 38 | 29 | 23 | 46   | 34 | 26 | 21 | 37   | 28 | 22 | 17 | 29   | 22 | 17 | 13 | 6   |
|        |           |                                   | 0.56            | 1.0  | 57                | 44 | 35 | 28 | 51   | 40 | 32 | 26 | 42   | 33 | 26 | 21 | 33   | 26 | 21 | 17 | 9   |
|        |           |                                   |                 | 1.25 | 62                | 50 | 41 | 34 | 56   | 46 | 38 | 32 | 46   | 38 | 31 | 26 | 36   | 30 | 25 | 21 | 11  |
| 下方投影面積 |           | cm <sup>2</sup>                   | 1.5             | 66   | 55                | 46 | 40 | 60 | 50   | 43 | 36 | 49 | 41   | 35 | 30 | 39 | 33   | 28 | 24 | 14 |     |
| 等価発光面積 |           |                                   | cm <sup>2</sup> | 2.0  | 72                | 62 | 54 | 48 | 66   | 57 | 50 | 44 | 54   | 47 | 41 | 37 | 43   | 38 | 33 | 29 | 18  |
|        |           |                                   |                 | 2.5  | 76                | 67 | 60 | 54 | 69   | 62 | 55 | 49 | 57   | 51 | 46 | 41 | 46   | 41 | 37 | 34 | 21  |
| 取付     | 器具間隔最大限   |                                   |                 | 3.0  | 79                | 71 | 64 | 58 | 72   | 65 | 59 | 54 | 60   | 54 | 49 | 45 | 48   | 44 | 40 | 37 | 24  |
| 高さ     | 横方向 ( A ) |                                   | 縦方向 ( B )       | 4.0  | 82                | 76 | 70 | 65 | 76   | 70 | 65 | 60 | 63   | 59 | 54 | 51 | 51   | 48 | 44 | 41 | 27  |
| H m    | 0.00 H m  |                                   | 0.00 H m        | 5.0  | 85                | 79 | 74 | 69 | 78   | 73 | 68 | 64 | 65   | 61 | 58 | 54 | 53   | 50 | 47 | 45 | 30  |
|        |           |                                   |                 | 7.0  | 88                | 83 | 79 | 75 | 81   | 77 | 73 | 70 | 68   | 65 | 62 | 59 | 56   | 54 | 51 | 49 | 34  |
|        |           |                                   |                 | 10.0 | 90                | 87 | 83 | 80 | 83   | 80 | 77 | 75 | 71   | 68 | 66 | 64 | 59   | 57 | 55 | 53 | 37  |

