

屋内照明器具特性	
品番 (品名)	L G W8 0 4 2 1
光源	LED5000_70_469 ×1 469.0 lm
管理番号	K0160259 (0) DR 1
B Z 分類	BZ10

器具効率		100 % 上方光束 50 % 下方光束	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
				床	10 %				10 %				10 %				10 %				0 %	
				室指数	照明率 (X0.01) ZCM																	
保守率		良 中 否	0.63	0.6	43	30	22	16	39	27	20	14	31	22	16	12	25	17	12	9	3	
			0.6	0.8	51	38	29	23	46	35	27	21	37	28	22	17	29	22	17	13	6	
			0.56	1.0	57	44	35	28	51	40	32	26	42	33	26	21	33	26	21	17	9	
				1.25	62	50	41	34	56	46	38	32	46	38	31	26	36	30	25	21	11	
下方投影面積		cm ²		1.5	66	55	47	40	60	50	43	37	49	42	35	30	39	33	28	24	14	
等価発光面積			cm ²	2.0	72	62	54	48	66	57	50	44	54	47	42	37	43	38	33	30	18	
					2.5	76	67	60	54	69	62	55	50	57	51	46	41	46	41	37	34	21
						3.0	79	71	64	58	72	65	59	54	60	54	49	45	48	44	40	37
H m	0.00 H m	0.00 H m				4.0	82	76	70	65	76	70	65	60	63	59	54	51	51	48	44	41
			5.0			85	79	74	69	78	73	68	64	65	61	58	54	53	50	47	45	30
			7.0	88		83	79	75	81	77	73	70	68	65	62	59	56	54	51	49	34	
			10.0	90	87	83	80	83	80	77	75	71	68	66	64	58	57	55	53	37		

