

屋内照明器具特性	
品番 (品名)	L S E B 4 0 2 8
光源	LED5000_70_460 ×1 460.0 l m
管理番号	K0151935 (0) DB 1
B Z 分類	B Z 6

器具効率		100 %	反射率	天井	80 %					70 %					50 %					30 %					0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %					
				床	10 %					10 %					10 %					10 %					0 %	
上方光束		28 %	室指数	照明率 (X0.01)																				Z	C	M
下方光束		72 %																								
保守率		良 中 否	0.63	0.6	49	36	28	23	46	35	27	22	41	31	25	20	36	28	23	19	15					
			0.6	0.8	58	46	38	32	55	44	36	30	49	40	33	28	43	36	30	26	21					
			0.56	1.0	64	53	44	38	61	50	43	37	54	45	39	34	48	41	35	31	26					
				1.25	70	59	51	45	66	56	49	43	59	51	45	40	52	46	41	37	30					
下方投影面積		c m ²	1.5	74	64	57	50	70	61	54	48	63	55	49	45	56	50	45	41	34						
等価発光面積			c m ²	2.0	80	71	64	58	76	68	62	56	68	61	56	52	60	55	51	47	40					
取付 高さ	器具間隔最大限		2.5	84	76	70	64	79	72	67	62	71	66	61	57	64	59	55	52	44						
	横方向 (A)		縦方向 (B)		3.0	86	79	74	69	82	76	71	66	74	69	64	61	66	62	59	55	47				
H m	1.46 H m		1.46 H m		4.0	90	84	79	75	85	80	76	72	77	73	69	66	69	66	63	60	51				
					5.0	92	87	83	79	87	83	79	76	79	76	73	70	71	68	66	64	54				
					7.0	94	91	87	84	90	87	84	81	82	79	77	74	74	72	70	68	58				
					10.0	96	94	91	89	92	90	87	85	84	82	80	78	76	74	73	71	61				

