

| 屋内照明器具特性 |                             |
|----------|-----------------------------|
| 品番 (品名)  | L S E B 5 8 0 0             |
| 光源       | LED5000_70_460 ×1 460.0 l m |
| 管理番号     | K0151698 ( 0 ) D 1          |
| B Z 分類   | B Z 3                       |

| 器具効率   |           | 100 %<br><br>上方光束<br>0 %<br>下方光束 | 反射率       | 天井   | 80 %               |     |     |     | 70 % |     |     |     | 50 % |     |     |    | 30 % |    |    |    | 0 % |
|--------|-----------|----------------------------------|-----------|------|--------------------|-----|-----|-----|------|-----|-----|-----|------|-----|-----|----|------|----|----|----|-----|
|        |           |                                  |           | 壁    | 70                 | 50  | 30  | 10  | 70   | 50  | 30  | 10  | 70   | 50  | 30  | 10 | 70   | 50 | 30 | 10 | 0 % |
|        |           |                                  |           | 床    | 10 %               |     |     |     | 10 % |     |     |     | 10 % |     |     |    | 10 % |    |    |    | 0 % |
|        |           |                                  |           | 室指数  | 照明率 ( X0.01) Z C M |     |     |     |      |     |     |     |      |     |     |    |      |    |    |    |     |
| 保守率    |           | 良<br>中<br>否                      | 0.67      | 0.6  | 64                 | 54  | 47  | 42  | 63   | 53  | 47  | 42  | 61   | 52  | 47  | 42 | 59   | 51 | 46 | 42 | 40  |
|        |           |                                  | 0.63      | 0.8  | 74                 | 65  | 58  | 54  | 73   | 64  | 58  | 54  | 71   | 63  | 58  | 53 | 69   | 62 | 57 | 53 | 51  |
|        |           |                                  | 0.56      | 1.0  | 81                 | 72  | 66  | 62  | 80   | 72  | 66  | 61  | 77   | 70  | 65  | 61 | 75   | 69 | 64 | 61 | 59  |
|        |           |                                  |           | 1.25 | 86                 | 79  | 73  | 69  | 85   | 78  | 73  | 68  | 82   | 76  | 72  | 68 | 80   | 75 | 71 | 67 | 66  |
| 下方投影面積 |           | cm <sup>2</sup>                  | 1.5       | 90   | 83                 | 78  | 74  | 88  | 82   | 77  | 73  | 86  | 81   | 76  | 73  | 83 | 79   | 75 | 72 | 70 |     |
|        |           |                                  | 等価発光面積    |      | cm <sup>2</sup>    | 2.0 | 94  | 89  | 84   | 81  | 93  | 88  | 84   | 80  | 90  | 86 | 83   | 79 | 88 | 84 | 81  |
| 取付     | 器具間隔最大限   |                                  |           | 2.5  | 97                 | 93  | 89  | 85  | 96   | 92  | 88  | 85  | 93   | 90  | 87  | 84 | 91   | 88 | 85 | 83 | 81  |
| 高さ     | 横方向 ( A ) |                                  | 縦方向 ( B ) | 3.0  | 99                 | 95  | 92  | 89  | 98   | 94  | 91  | 88  | 95   | 92  | 89  | 87 | 93   | 90 | 88 | 86 | 83  |
| H m    | 1.15 H m  |                                  | 1.15 H m  | 4.0  | 101                | 98  | 95  | 93  | 100  | 97  | 95  | 92  | 98   | 95  | 93  | 91 | 95   | 93 | 91 | 90 | 87  |
|        |           |                                  |           | 5.0  | 103                | 100 | 98  | 96  | 102  | 99  | 97  | 95  | 99   | 97  | 95  | 94 | 97   | 95 | 94 | 92 | 90  |
|        |           |                                  |           | 7.0  | 104                | 102 | 101 | 99  | 103  | 101 | 100 | 98  | 101  | 99  | 98  | 97 | 98   | 97 | 96 | 95 | 92  |
|        |           |                                  |           | 10.0 | 106                | 104 | 103 | 102 | 104  | 103 | 102 | 101 | 102  | 101 | 100 | 99 | 100  | 99 | 98 | 97 | 94  |

