

屋内照明器具特性	
品番 (品名)	NNN60003S
光源	LDT1L-H-E12 ×1 10.0lm
管理番号	K0153667 (1) DR1
BZ分類	BZ1

器具効率		71 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) ZCM																
保守率		良 中 否	0.67	0.6	63	59	57	55	62	59	57	55	61	59	57	55	61	58	56	55	54
			0.63	0.8	66	63	61	59	66	63	61	59	65	62	61	59	64	62	60	59	58
			0.56	1.0	68	66	64	62	68	65	63	62	67	65	63	62	66	64	63	61	61
				1.25	70	68	66	64	70	67	66	64	68	67	65	64	67	66	65	64	63
下方投影面積		cm ²		1.5	71	69	67	66	71	69	67	66	69	68	66	65	68	67	66	65	64
			等価発光面積	cm ²	2.0	73	71	69	68	72	70	69	68	71	69	68	67	70	68	67	67
取付 高さ	器具間隔最大限			2.5	73	72	71	70	73	71	70	69	71	70	69	68	70	69	68	68	66
	横方向 (A) 縦方向 (B)			3.0	74	73	72	71	73	72	71	70	72	71	70	69	71	70	69	69	67
H m	1.14 H m 1.14 H m			4.0	75	74	73	72	74	73	72	71	73	72	71	70	71	71	70	69	68
				5.0	75	74	74	73	74	74	73	72	73	72	72	71	72	71	71	70	68
				7.0	76	75	74	74	75	74	74	73	73	73	72	72	72	72	71	71	69
				10.0	76	76	75	75	75	75	74	74	74	73	73	73	72	72	72	71	69

