

| 屋内照明器具特性 |                                |
|----------|--------------------------------|
| 品番 (品名)  | XLX111REW                      |
| 光源       | LED4000_85_11370 ×1 11370.0 lm |
| 管理番号     | K0154865 (8) D 1               |
| BZ分類     | BZ5/0.9/BZ4                    |

| 器具効率         |                     | 100 %           | 反射率  | 天井                | 80 % |     |     |     | 70 % |     |    |     | 50 % |    |    |    | 30 % |    |    |    | 0 % |  |  |
|--------------|---------------------|-----------------|------|-------------------|------|-----|-----|-----|------|-----|----|-----|------|----|----|----|------|----|----|----|-----|--|--|
|              |                     |                 |      | 壁                 | 70   | 50  | 30  | 10  | 70   | 50  | 30 | 10  | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 0 % |  |  |
|              |                     |                 |      | 床                 | 10 % |     |     |     | 10 % |     |    |     | 10 % |    |    |    | 10 % |    |    |    | 0 % |  |  |
| 上方光束<br>下方光束 |                     | 100 %           | 室指数  | 照明率 ( X0.01 ) ZCM |      |     |     |     |      |     |    |     |      |    |    |    |      |    |    |    |     |  |  |
| 保守率          |                     | 良<br>中<br>否     | 0.81 | 0.6               | 57   | 45  | 38  | 32  | 56   | 45  | 37 | 32  | 54   | 44 | 37 | 32 | 52   | 43 | 36 | 32 | 30  |  |  |
|              |                     |                 | 0.77 | 0.8               | 68   | 56  | 49  | 43  | 66   | 56  | 48 | 43  | 64   | 54 | 48 | 43 | 61   | 53 | 47 | 42 | 40  |  |  |
|              |                     |                 | 0.68 | 1.0               | 74   | 64  | 57  | 51  | 73   | 63  | 56 | 51  | 70   | 62 | 55 | 50 | 67   | 60 | 55 | 50 | 48  |  |  |
|              |                     |                 |      | 1.25              | 81   | 71  | 64  | 59  | 79   | 70  | 64 | 58  | 76   | 69 | 63 | 58 | 73   | 67 | 62 | 58 | 55  |  |  |
| 下方投影面積       |                     | cm <sup>2</sup> | 1.5  | 85                | 76   | 70  | 64  | 83  | 75   | 69  | 64 | 80  | 73   | 68 | 64 | 77 | 72   | 67 | 63 | 61 |     |  |  |
| 等価発光面積       |                     | cm <sup>2</sup> | 2.0  | 90                | 83   | 78  | 73  | 89  | 82   | 77  | 73 | 86  | 80   | 76 | 72 | 83 | 78   | 74 | 71 | 69 |     |  |  |
| 取付<br>高さ     | 器具間隔最大限             |                 | 2.5  | 94                | 88   | 83  | 79  | 92  | 87   | 82  | 78 | 89  | 85   | 81 | 77 | 87 | 83   | 79 | 76 | 74 |     |  |  |
|              | 横方向 ( A ) 縦方向 ( B ) |                 | 3.0  | 96                | 91   | 87  | 83  | 95  | 90   | 86  | 82 | 92  | 88   | 84 | 81 | 89 | 86   | 83 | 80 | 78 |     |  |  |
| 1.5m         | 1.92 m              | 1.91 m          | 4.0  | 99                | 95   | 92  | 89  | 98  | 94   | 91  | 88 | 95  | 92   | 89 | 87 | 93 | 90   | 88 | 85 | 83 |     |  |  |
| 2            | 2.54                | 2.53            | 5.0  | 101               | 98   | 95  | 92  | 100 | 97   | 94  | 91 | 97  | 95   | 92 | 90 | 95 | 92   | 90 | 89 | 86 |     |  |  |
| 2.5          | 3.17                | 3.17            | 7.0  | 103               | 101  | 99  | 97  | 102 | 100  | 98  | 96 | 99  | 97   | 96 | 94 | 97 | 95   | 94 | 92 | 90 |     |  |  |
| 3            | 3.81                | 3.8             | 10.0 | 105               | 103  | 101 | 100 | 103 | 102  | 100 | 99 | 101 | 100  | 98 | 97 | 99 | 98   | 96 | 95 | 93 |     |  |  |

