

屋内照明器具特性	
品番 (品名)	XLX110REN
光源	LED5000_85_12000 ×1 12000.0 lm
管理番号	K0154865 (8) D 1
BZ分類	BZ5/0.9/BZ4

器具効率			100 %		反射率	天井	80 %					70 %					50 %					30 %					0 %
						壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
						床	10 %					10 %					10 %					10 %					0 %
						照明率 (X0.01) ZCM																					
保守率			良 中 否	0.81	0.6	57	45	38	32	56	45	37	32	54	44	37	32	52	43	36	32	30					
				0.77	0.8	68	56	49	43	66	56	48	43	64	54	48	43	61	53	47	42	40					
				0.68	1.0	74	64	57	51	73	63	56	51	70	62	55	50	67	60	55	50	48					
					1.25	81	71	64	59	79	70	64	58	76	69	63	58	73	67	62	58	55					
下方投影面積			cm ²	1.5	85	76	70	64	83	75	69	64	80	73	68	64	77	72	67	63	61						
				2.0	90	83	78	73	89	82	77	73	86	80	76	72	83	78	74	71	69						
等価発光面積			cm ²	2.5	94	88	83	79	92	87	82	78	89	85	81	77	87	83	79	76	74						
				3.0	96	91	87	83	95	90	86	82	92	88	84	81	89	86	83	80	78						
1.5m		1.92 m	1.91 m	4.0	99	95	92	89	98	94	91	88	95	92	89	87	93	90	88	85	83						
2		2.54	2.53	5.0	101	98	95	92	100	97	94	91	97	95	92	90	95	92	90	89	86						
2.5		3.17	3.17	7.0	103	101	99	97	102	100	98	96	99	97	96	94	97	95	94	92	90						
3		3.81	3.8	10.0	105	103	101	100	103	102	100	99	101	100	98	97	99	98	96	95	93						

