

# 屋内照明器具特性

品番 (品名)	LGBZ1434									
光源	LED6200_70_4299 x1 4299.0 lm									
管理番号	K0145472(0)DB1									
BZ分類	BZ8/0.9/BZ7/2.8/BZ6									

器具効率	100%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束	6%	室指数																			
下方光束	94%	照明率 ( X0.01) ZCM																			
保守率	良 中 否 0.63 0.6 0.56	0.6	47	33	24	18	46	32	24	18	42	31	23	17	39	29	22	17	14		
		0.8	57	43	33	26	55	42	33	26	51	39	31	25	47	37	30	25	22		
		1.0	63	50	40	33	61	48	39	32	57	46	38	32	53	43	36	31	27		
		1.25	69	57	47	40	67	55	46	40	62	53	45	38	58	50	43	37	34		
下方投影面積	c m <sup>2</sup>	1.5	74	62	53	46	72	61	52	45	67	58	50	44	63	55	48	43	39		
		2.0	81	71	62	55	78	69	61	55	73	66	59	53	69	62	57	52	48		
取付高さ	器具間隔最大限		2.5	85	76	69	62	83	74	67	61	78	71	65	60	73	68	63	58	54	
	横方向 (A)	縦方向 (B)	3.0	88	80	74	68	86	79	72	67	81	75	70	65	77	72	67	63	59	
H m	1.82 H m	1.76 H m	4.0	92	86	80	75	90	84	79	74	86	81	76	72	81	77	73	70	66	
			5.0	95	90	85	80	93	88	83	79	88	84	80	77	84	81	78	75	70	
			7.0	98	94	90	87	96	92	89	85	92	89	86	83	88	85	83	80	76	
			10.0	101	98	95	92	99	96	93	91	95	92	90	88	91	89	87	85	81	

