

| 屋内照明器具特性 |                              |
|----------|------------------------------|
| 品番 (品名)  | XLX130REL                    |
| 光源       | LED3000_85_2710 ×1 2710.0 lm |
| 管理番号     | K0154865 ( 8 ) D 1           |
| BZ分類     | BZ5 / 0.9 / BZ4              |

| 器具効率     |                     | 100 %<br><br>上方光束<br>0 %<br>下方光束 | 反射率    | 天井  | 80 %              |     |     |     | 70 % |     |    |     | 50 % |    |    |    | 30 % |    |    |    | 0 % |
|----------|---------------------|----------------------------------|--------|-----|-------------------|-----|-----|-----|------|-----|----|-----|------|----|----|----|------|----|----|----|-----|
|          |                     |                                  |        | 壁   | 70                | 50  | 30  | 10  | 70   | 50  | 30 | 10  | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 0 % |
|          |                     |                                  |        | 床   | 10 %              |     |     |     | 10 % |     |    |     | 10 % |    |    |    | 10 % |    |    |    | 0 % |
|          |                     |                                  |        | 室指数 | 照明率 ( X0.01 ) ZCM |     |     |     |      |     |    |     |      |    |    |    |      |    |    |    |     |
| 保守率      |                     | 良<br>中<br>否                      | 0.6    | 57  | 45                | 38  | 32  | 56  | 45   | 37  | 32 | 54  | 44   | 37 | 32 | 52 | 43   | 36 | 32 | 30 |     |
|          |                     |                                  | 0.8    | 68  | 56                | 49  | 43  | 66  | 56   | 48  | 43 | 64  | 54   | 48 | 43 | 61 | 53   | 47 | 42 | 40 |     |
|          |                     |                                  | 1.0    | 74  | 64                | 57  | 51  | 73  | 63   | 56  | 51 | 70  | 62   | 55 | 50 | 67 | 60   | 55 | 50 | 48 |     |
|          |                     |                                  | 1.25   | 81  | 71                | 64  | 59  | 79  | 70   | 64  | 58 | 76  | 69   | 63 | 58 | 73 | 67   | 62 | 58 | 55 |     |
| 下方投影面積   |                     | cm <sup>2</sup>                  | 1.5    | 85  | 76                | 70  | 64  | 83  | 75   | 69  | 64 | 80  | 73   | 68 | 64 | 77 | 72   | 67 | 63 | 61 |     |
|          |                     |                                  | 等価発光面積 |     | cm <sup>2</sup>   | 2.0 | 90  | 83  | 78   | 73  | 89 | 82  | 77   | 73 | 86 | 80 | 76   | 72 | 83 | 78 | 74  |
| 取付<br>高さ | 器具間隔最大限             |                                  | 2.5    | 94  | 88                | 83  | 79  | 92  | 87   | 82  | 78 | 89  | 85   | 81 | 77 | 87 | 83   | 79 | 76 | 74 |     |
|          | 横方向 ( A ) 縦方向 ( B ) |                                  | 3.0    | 96  | 91                | 87  | 83  | 95  | 90   | 86  | 82 | 92  | 88   | 84 | 81 | 89 | 86   | 83 | 80 | 78 |     |
| 1.5m     | 1.92 m              | 1.91 m                           | 4.0    | 99  | 95                | 92  | 89  | 98  | 94   | 91  | 88 | 95  | 92   | 89 | 87 | 93 | 90   | 88 | 85 | 83 |     |
| 2        | 2.54                | 2.53                             | 5.0    | 101 | 98                | 95  | 92  | 100 | 97   | 94  | 91 | 97  | 95   | 92 | 90 | 95 | 92   | 90 | 89 | 86 |     |
| 2.5      | 3.17                | 3.17                             | 7.0    | 103 | 101               | 99  | 97  | 102 | 100  | 98  | 96 | 99  | 97   | 96 | 94 | 97 | 95   | 94 | 92 | 90 |     |
| 3        | 3.81                | 3.8                              | 10.0   | 105 | 103               | 101 | 100 | 103 | 102  | 100 | 99 | 101 | 100  | 98 | 97 | 99 | 98   | 96 | 95 | 93 |     |

