

屋内照明器具特性	
品番 (品名)	X L Y 0 9 0 H W
光源	L E D 4 0 0 0 _ 8 5 _ 2 1 9 0 × 1 2 1 9 0 . 0 l m
管理番号	K 0 1 5 5 4 0 8 (0) D B 1
B Z 分類	B Z 5

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
				室指数	照明率 (X 0 . 0 1) Z C M																
保守率		良 中 否	0 . 8 3	0 . 6	5 4	4 2	3 4	2 8	5 3	4 1	3 3	2 8	4 9	3 9	3 2	2 7	4 7	3 8	3 2	2 7	2 5
			0 . 8 1	0 . 8	6 4	5 2	4 4	3 8	6 2	5 1	4 3	3 8	5 8	4 9	4 2	3 7	5 5	4 7	4 1	3 6	3 3
			0 . 7 7	1 . 0	7 0	5 9	5 1	4 5	6 8	5 8	5 0	4 4	6 4	5 5	4 9	4 4	6 1	5 3	4 7	4 3	4 0
				1 . 2 5	7 6	6 6	5 8	5 2	7 4	6 5	5 7	5 2	7 0	6 2	5 6	5 0	6 6	5 9	5 4	4 9	4 6
下方投影面積		c m ²	1 . 5	8 0	7 1	6 3	5 8	7 8	6 9	6 2	5 7	7 4	6 6	6 1	5 6	7 0	6 4	5 9	5 4	5 1	
			等価発光面積	c m ²	2 . 0	8 6	7 8	7 1	6 6	8 4	7 6	7 0	6 5	7 9	7 3	6 8	6 3	7 5	7 0	6 6	6 2
取付高さ	器具間隔最大限		2 . 5	9 0	8 3	7 7	7 2	8 7	8 1	7 5	7 1	8 3	7 8	7 3	6 9	7 9	7 4	7 0	6 7	6 3	
	横方向 (A)	縦方向 (B)	3 . 0	9 2	8 6	8 1	7 6	9 0	8 4	7 9	7 5	8 6	8 1	7 7	7 3	8 2	7 8	7 4	7 1	6 7	
1 . 5m	1 . 9 8 m	2 . 0 2 m	4 . 0	9 5	9 0	8 6	8 2	9 3	8 9	8 4	8 1	8 9	8 5	8 2	7 8	8 5	8 2	7 9	7 6	7 2	
2	2 . 6 2	2 . 6	5 . 0	9 7	9 3	8 9	8 6	9 5	9 1	8 8	8 5	9 1	8 8	8 5	8 2	8 7	8 5	8 2	8 0	7 5	
2 . 5	3 . 2 5	3 . 2 1	7 . 0	1 0 0	9 7	9 4	9 1	9 8	9 5	9 2	8 9	9 4	9 1	8 9	8 7	9 0	8 8	8 6	8 4	7 9	
3	3 . 8 9	3 . 8 1	1 0 . 0	1 0 2	9 9	9 7	9 5	1 0 0	9 8	9 5	9 3	9 6	9 4	9 2	9 0	9 2	9 0	8 9	8 8	8 3	

