

屋内照明器具特性	
品番 (品名)	L G B 1 5 0 9 9
光源	LDG11L - G / 95 / W ×1 1370.0 l m
管理番号	K0161033 (0) DB 1
B Z 分類	BZ7 / 0.7 / BZ6

器具効率		93 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) Z C M																
保守率		良 中 否	0.67	0.6	46	34	26	21	43	32	25	20	39	29	23	19	34	27	21	17	14
			0.63	0.8	54	43	35	29	51	41	33	28	46	37	31	26	41	34	28	24	20
			0.56	1.0	60	49	41	35	57	47	40	34	51	43	36	32	45	39	33	29	25
				1.25	65	55	48	42	62	53	46	40	56	48	42	38	50	44	39	35	29
下方投影面積 等価発光面積		c m ²		1.5	69	60	53	47	66	57	51	45	59	52	47	42	53	48	43	39	33
				2.0	75	67	60	55	71	64	58	53	64	59	54	49	58	53	49	46	39
				2.5	78	72	66	61	75	69	63	59	68	63	58	55	61	57	54	50	43
				3.0	81	75	70	65	77	72	67	63	70	66	62	58	64	60	57	54	47
H m	1.42 H m	1.42 H m		4.0	84	79	75	71	81	76	72	69	73	70	67	64	67	64	61	59	51
				5.0	86	82	78	75	83	79	75	72	75	72	70	67	69	66	64	62	54
				7.0	89	86	83	80	85	82	80	77	78	76	73	71	71	69	68	66	58
				10.0	91	88	86	84	87	85	83	81	80	78	77	75	73	72	70	69	61

