

# 屋内照明器具特性

|         |                              |  |  |  |  |  |  |  |  |  |
|---------|------------------------------|--|--|--|--|--|--|--|--|--|
| 品番 (品名) | XLX460FBVJ                   |  |  |  |  |  |  |  |  |  |
| 光源      | LED3500_85_4570 x1 4570.0 lm |  |  |  |  |  |  |  |  |  |
| 管理番号    | K0132392(1)DB1               |  |  |  |  |  |  |  |  |  |
| BZ分類    | BZ4                          |  |  |  |  |  |  |  |  |  |

|        |                  |         |              |      |      |      |      |      |      |      |     |      |      |     |     |     |     |     |     |     |
|--------|------------------|---------|--------------|------|------|------|------|------|------|------|-----|------|------|-----|-----|-----|-----|-----|-----|-----|
| 器具効率   | 100%             | 天井      | 80%          |      |      |      | 70%  |      |      |      | 50% |      |      |     | 30% |     |     |     | 0%  |     |
|        |                  |         | 壁            | 70   | 50   | 30   | 10   | 70   | 50   | 30   | 10  | 70   | 50   | 30  | 10  | 70  | 50  | 30  | 10  | 0%  |
|        |                  |         |              | 床    | 10%  |      |      |      | 10%  |      |     |      | 10%  |     |     |     | 10% |     |     |     |
| 上方光束   | 0%               | 室指数     | 照明率 ( X0.01) |      |      |      |      |      |      |      |     |      |      |     |     |     |     |     | ZCM |     |
| 下方光束   | 100%             |         |              |      |      |      |      |      |      |      |     |      |      |     |     |     |     |     |     |     |
| 保守率    | 良<br>中<br>否      | 0.81    | 0.6          | 5.9  | 4.7  | 4.0  | 3.5  | 5.8  | 4.7  | 4.0  | 3.5 | 5.5  | 4.6  | 3.9 | 3.4 | 5.3 | 4.5 | 3.9 | 3.4 | 3.2 |
|        |                  | 0.77    | 0.8          | 7.0  | 5.9  | 5.1  | 4.6  | 6.8  | 5.8  | 5.1  | 4.6 | 6.6  | 5.7  | 5.0 | 4.6 | 6.3 | 5.5 | 5.0 | 4.5 | 4.3 |
|        |                  | 0.68    | 1.0          | 7.6  | 6.6  | 5.9  | 5.4  | 7.5  | 6.6  | 5.9  | 5.4 | 7.2  | 6.4  | 5.8 | 5.4 | 7.0 | 6.3 | 5.7 | 5.3 | 5.1 |
|        |                  |         | 1.25         | 8.2  | 7.3  | 6.7  | 6.2  | 8.1  | 7.3  | 6.6  | 6.1 | 7.8  | 7.1  | 6.5 | 6.1 | 7.5 | 6.9 | 6.4 | 6.0 | 5.8 |
| 下方投影面積 | c m <sup>2</sup> | 1.5     | 8.6          | 7.8  | 7.2  | 6.7  | 8.5  | 7.7  | 7.1  | 6.7  | 8.2 | 7.5  | 7.0  | 6.6 | 7.9 | 7.4 | 6.9 | 6.6 | 6.3 |     |
|        |                  | 2.0     | 9.1          | 8.5  | 8.0  | 7.5  | 9.0  | 8.4  | 7.9  | 7.5  | 8.7 | 8.2  | 7.8  | 7.4 | 8.4 | 8.0 | 7.6 | 7.3 | 7.1 |     |
| 取付高さ   | 器具間隔最大限          |         | 2.5          | 9.5  | 8.9  | 8.4  | 8.0  | 9.3  | 8.8  | 8.4  | 8.0 | 9.0  | 8.6  | 8.2 | 7.9 | 8.8 | 8.4 | 8.1 | 7.8 | 7.6 |
|        | 横方向 (A)          | 縦方向 (B) | 3.0          | 9.7  | 9.2  | 8.8  | 8.4  | 9.5  | 9.1  | 8.7  | 8.4 | 9.3  | 8.9  | 8.6 | 8.3 | 9.0 | 8.7 | 8.4 | 8.2 | 7.9 |
| 1.5m   | 2.03m            | 2.18m   | 4.0          | 10.0 | 9.6  | 9.2  | 8.9  | 9.8  | 9.5  | 9.2  | 8.9 | 9.5  | 9.3  | 9.0 | 8.7 | 9.3 | 9.1 | 8.8 | 8.6 | 8.4 |
| 2      | 2.68             | 2.74    | 5.0          | 10.1 | 9.8  | 9.5  | 9.3  | 10.0 | 9.7  | 9.4  | 9.2 | 9.7  | 9.5  | 9.3 | 9.1 | 9.5 | 9.3 | 9.1 | 8.9 | 8.6 |
| 2.5    | 3.33             | 3.34    | 7.0          | 10.3 | 10.1 | 9.9  | 9.7  | 10.2 | 10.0 | 9.8  | 9.6 | 9.9  | 9.8  | 9.6 | 9.4 | 9.7 | 9.5 | 9.4 | 9.3 | 9.0 |
| 3      | 3.98             | 3.94    | 10.0         | 10.5 | 10.3 | 10.1 | 10.0 | 10.3 | 10.2 | 10.0 | 9.9 | 10.1 | 10.0 | 9.8 | 9.7 | 9.9 | 9.7 | 9.6 | 9.5 | 9.3 |

