

屋内照明器具特性

品番 (品名)	NNF 15903				
光源	LED3000_85_660 x1 660.0 l m				
管理番号	K0144293 (0) DD 1				
BZ分類	BZ1				

器具効率	100%	天井	80%				70%				50%				30%				0%		
	上方光束		0%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		100%		床	10%				10%				10%				10%			
室指数	照明率 (X0.01) ZCM																				
保守率	良	0.77	0.6	76	69	64	60	76	68	64	60	74	68	63	60	72	67	63	60	59	
	中	0.72	0.8	84	77	73	69	83	77	72	69	81	76	72	69	80	75	71	69	67	
	否	0.68	1.0	89	83	79	75	88	82	78	75	86	81	78	75	84	80	77	74	73	
			1.25	93	88	84	80	92	87	83	80	90	86	82	80	88	84	81	79	78	
下方投影面積	c m ²		1.5	95	91	87	84	94	90	86	84	92	88	85	83	90	87	85	82	81	
	等価発光面積		c m ²	2.0	99	95	92	89	97	94	91	88	95	92	90	88	93	91	89	87	85
取付高さ	器具間隔最大限		2.5	100	97	94	92	99	96	94	92	97	95	92	90	95	93	91	89	87	
	H m	0.86 H m	0.86 H m	3.0	102	99	96	94	101	98	96	94	98	96	94	93	96	94	93	91	89
				4.0	103	101	99	97	102	100	98	97	100	98	97	95	98	96	95	94	92
				5.0	104	102	101	99	103	101	100	98	101	99	98	97	99	98	96	95	93
				7.0	105	104	103	102	104	103	102	101	102	101	100	99	100	99	98	97	95
				10.0	106	105	104	103	105	104	103	102	103	102	101	101	100	99	99	99	96

