

屋内照明器具特性	
品番 (品名)	L G W8 0 2 6 4
光源	LED2700_70_263 ×1 263.0 l m
管理番号	K0160972 (0) DB 1
BZ分類	BZ8/0.7/BZ7/0.9/BZ6/4.5/BZ5

器具効率		1 0 0 %	反射率	天井	8 0 %					7 0 %					5 0 %					3 0 %					0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %				
				床	1 0 %					1 0 %					1 0 %					1 0 %					0 %
上方光束		6 %	室指数	照明率 (X 0 . 0 1)																				Z C M	
下方光束		9 4 %																							
保守率		良 中 否	0 . 6 3	0 . 6	4 8	3 4	2 5	1 9	4 6	3 3	2 4	1 8	4 3	3 1	2 4	1 8	4 0	3 0	2 3	1 8	1 5				
			0 . 6	0 . 8	5 8	4 5	3 6	2 9	5 6	4 4	3 5	2 9	5 2	4 2	3 4	2 8	4 9	4 0	3 3	2 7	2 4				
			0 . 5 6	1 . 0	6 6	5 3	4 4	3 7	6 3	5 2	4 3	3 7	5 9	4 9	4 2	3 6	5 5	4 7	4 0	3 5	3 2				
				1 . 2 5	7 2	6 1	5 2	4 5	7 0	5 9	5 1	4 5	6 6	5 7	4 9	4 4	6 2	5 4	4 8	4 3	3 9				
下方投影面積		c m ²	1 . 5	7 7	6 7	5 9	5 2	7 5	6 5	5 8	5 1	7 1	6 2	5 6	5 0	6 6	5 9	5 4	4 9	4 5					
			2 . 0	8 4	7 5	6 8	6 2	8 2	7 3	6 7	6 1	7 7	7 0	6 4	5 9	7 3	6 7	6 2	5 8	5 4					
取付高さ	器具間隔最大限		2 . 5	8 8	8 1	7 4	6 9	8 6	7 9	7 3	6 8	8 1	7 5	7 0	6 6	7 7	7 2	6 8	6 4	6 0					
	横方向 (A)	縦方向 (B)	3 . 0	9 1	8 4	7 9	7 4	8 9	8 3	7 7	7 3	8 4	7 9	7 5	7 1	8 0	7 6	7 2	6 9	6 5					
H m	0 . 0 0 H m	0 . 0 0 H m	4 . 0	9 5	8 9	8 5	8 0	9 3	8 8	8 3	7 9	8 8	8 4	8 0	7 7	8 4	8 1	7 8	7 5	7 1					
			5 . 0	9 7	9 3	8 8	8 5	9 5	9 1	8 7	8 3	9 1	8 7	8 4	8 1	8 7	8 4	8 1	7 9	7 4					
			7 . 0	1 0 0	9 6	9 3	9 0	9 8	9 4	9 2	8 9	9 4	9 1	8 8	8 6	9 0	8 8	8 6	8 4	7 9					
			1 0 . 0	1 0 2	9 9	9 7	9 5	1 0 0	9 7	9 5	9 3	9 6	9 4	9 2	9 0	9 2	9 0	8 9	8 7	8 3					

