

屋内照明器具特性

品番 (品名)	LGB52612									
光源	LED5000_70_1700 x1					1700.0 lm				
管理番号	K0147582(0)DB1									
BZ分類	BZ6/0.7/BZ5/2.8/BZ6									

器具効率	100%	天井	80%				70%				50%				30%				0%		
	上方光束 9%		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
下方光束	91%	床		10%				10%				10%				10%				0%	
室指数	照明率 (X0.01)																				ZCM
保守率	良	0.63	0.6	53	41	33	27	51	40	32	27	48	38	31	26	45	36	30	25	23	
	中	0.6	0.8	63	51	42	36	61	49	42	36	57	47	40	35	53	45	39	34	31	
	否	0.56	1.0	69	58	49	43	67	56	49	43	63	54	47	42	59	51	45	40	37	
			1.25	75	64	56	50	72	63	55	50	68	60	53	48	64	57	51	47	43	
下方投影面積	cm ²		1.5	79	69	62	56	77	68	60	55	72	64	58	53	68	61	56	52	48	
等価発光面積	cm ²		2.0	85	76	69	64	82	74	68	63	77	71	65	61	73	67	63	59	55	
取付高さ	器具間隔最大限		2.5	88	81	75	69	86	79	73	68	81	75	70	66	76	72	68	64	60	
	横方向 (A)	縦方向 (B)	3.0	91	84	79	74	88	82	77	73	83	78	74	70	79	75	71	68	63	
H _m	1.30H _m	1.30H _m	4.0	94	89	84	80	92	87	82	79	87	83	79	76	82	79	76	73	68	
			5.0	96	92	88	84	94	90	86	82	89	86	82	80	85	82	79	77	72	
			7.0	99	95	92	89	96	93	90	87	92	89	87	84	87	85	83	81	76	
			10.0	101	98	96	93	98	96	94	92	94	92	90	88	90	88	86	85	80	

