

屋内照明器具特性	
品番 (品名)	L G W8 0 2 2 0 K
光源	LED2700_70_195 ×1 195.0 l m
管理番号	K0158606 (0) DB 1
B Z 分類	B Z 5

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %			
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
				床	10 %				10 %				10 %				10 %				0 %			
上方光束		50 %	室指数	照明率 (X0.01)																		Z	C	M
下方光束		50 %																						
保守率		良 中 否	0.63	0.6	49	37	30	25	45	35	28	24	38	30	25	21	31	25	21	18	13			
			0.6	0.8	58	47	39	34	53	43	37	32	45	37	32	28	37	31	27	24	18			
			0.56	1.0	64	53	46	40	59	50	43	38	50	43	37	33	41	36	32	29	21			
				1.25	69	60	53	47	64	56	49	44	54	48	43	39	45	40	36	33	24			
下方投影面積		cm ²	1.5	73	65	58	52	68	60	54	49	57	51	47	43	48	43	40	37	27				
等価発光面積		cm ²	2.0	79	71	65	60	73	66	61	57	62	57	53	49	51	48	45	42	31				
取付 高さ	器具間隔最大限		2.5	82	76	70	66	76	70	66	62	64	60	57	54	54	51	48	46	34				
	横方向 (A)		縦方向 (B)	3.0	84	79	74	70	78	73	69	65	66	63	60	57	56	53	50	48	36			
1.5m	1.97 m	1.96 m	4.0	87	83	79	75	81	77	74	71	69	66	64	61	58	56	54	52	38				
2	2.63	2.59	5.0	89	85	82	79	83	80	77	74	71	68	66	64	59	58	56	54	40				
2.5	3.29	3.24	7.0	91	89	86	83	85	83	80	78	73	71	69	68	61	60	59	57	42				
3	3.95	3.89	10.0	93	91	89	87	87	85	83	81	74	73	72	70	63	62	61	60	44				

