

屋内照明器具特性

品番 (品名)	L G W J 5 0 1 2 9 K									
光源	L E D 2 7 0 0 _ 7 0 _ 8 5 x 1 8 5 . 0 l m									
管理番号	K 0 1 5 8 8 4 6 (0) D B 1									
B Z 分類	B Z 1 0									

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束 下方光束		5 4 % 4 6 %	室指数	照明率 (X 0 . 0 1) Z C M																		
保守率		良 中 否	0 . 6 3	0 . 6	4 1	2 8	2 0	1 4	3 7	2 5	1 8	1 2	2 9	2 0	1 4	9	2 2	1 5	1 0	6	0	
			0 . 6	0 . 8	4 8	3 5	2 6	1 9	4 3	3 1	2 3	1 7	3 4	2 4	1 8	1 3	2 5	1 8	1 3	9	1	
			0 . 5 6	1 . 0	5 3	4 0	3 1	2 3	4 8	3 6	2 7	2 1	3 7	2 8	2 1	1 6	2 8	2 1	1 5	1 1	2	
				1 . 2 5	5 8	4 5	3 6	2 8	5 2	4 1	3 2	2 5	4 1	3 2	2 5	1 9	3 0	2 3	1 8	1 3	3	
下方投影面積		c m ²		1 . 5	6 2	5 0	4 0	3 2	5 5	4 4	3 6	2 9	4 3	3 5	2 8	2 2	3 2	2 6	2 0	1 6	5	
等価発光面積			c m ²	2 . 0	6 7	5 6	4 7	3 9	6 0	5 0	4 2	3 5	4 7	4 0	3 3	2 7	3 6	2 9	2 4	2 0	7	
取付 高さ	器具間隔最大限		2 . 5	7 1	6 0	5 2	4 4	6 4	5 5	4 7	4 0	5 1	4 3	3 7	3 1	3 8	3 2	2 7	2 3	9		
	横方向 (A) 縦方向 (B)		3 . 0	7 3	6 4	5 6	4 8	6 6	5 8	5 0	4 4	5 3	4 6	4 0	3 5	4 0	3 5	3 0	2 6	1 1		
1 . 5m	0 m	0 m	4 . 0	7 7	6 9	6 2	5 5	7 0	6 3	5 6	5 0	5 6	5 0	4 5	4 0	4 3	3 9	3 4	3 0	1 5		
2	0	0	5 . 0	8 0	7 2	6 6	6 0	7 3	6 6	6 0	5 4	5 9	5 3	4 8	4 4	4 6	4 1	3 7	3 4	1 8		
2 . 5	0	0	7 . 0	8 3	7 7	7 2	6 6	7 6	7 0	6 5	6 1	6 2	5 7	5 3	4 9	4 9	4 5	4 2	3 9	2 2		
3	0	0	1 0 . 0	8 6	8 1	7 7	7 2	7 9	7 4	7 0	6 6	6 5	6 1	5 8	5 5	5 2	4 9	4 6	4 3	2 6		

