

| 屋内照明器具特性 |                                           |
|----------|-------------------------------------------|
| 品番 (品名)  | L G B 1 5 3 2 4 K                         |
| 光源       | LDA13L - G / Z100E / S / W × 4 1520.0 l m |
| 管理番号     | K0195545 ( 2 ) D 1                        |
| B Z 分類   | B Z 6                                     |

| 器具効率     |                 | 67 %        | 反射率      | 天井              | 80 % |      |               |    |    | 70 % |      |    |    |    | 50 % |      |    |    |    | 30 % |      |    |    |    | 0 % |     |
|----------|-----------------|-------------|----------|-----------------|------|------|---------------|----|----|------|------|----|----|----|------|------|----|----|----|------|------|----|----|----|-----|-----|
|          |                 |             |          | 壁               | 70   | 50   | 30            | 10 | 70 | 50   | 30   | 10 | 70 | 50 | 30   | 10   | 70 | 50 | 30 | 10   | 70   | 50 | 30 | 10 | 0 % |     |
|          |                 |             |          |                 | 床    | 10 % |               |    |    |      | 10 % |    |    |    |      | 10 % |    |    |    |      | 10 % |    |    |    |     | 0 % |
|          |                 |             |          |                 |      | 室指数  | 照明率 ( X0.01 ) |    |    |      |      |    |    |    |      |      |    |    |    |      |      |    |    |    |     |     |
| 保守率      |                 | 良<br>中<br>否 | 0.67     | 0.6             | 33   | 25   | 19            | 16 | 31 | 23   | 18   | 15 | 27 | 21 | 17   | 14   | 24 | 19 | 15 | 12   | 10   |    |    |    |     |     |
|          |                 |             | 0.63     | 0.8             | 39   | 31   | 26            | 22 | 37 | 29   | 24   | 21 | 32 | 26 | 22   | 19   | 28 | 23 | 20 | 17   | 14   |    |    |    |     |     |
|          |                 |             | 0.56     | 1.0             | 43   | 36   | 30            | 26 | 41 | 34   | 29   | 25 | 36 | 30 | 26   | 23   | 31 | 27 | 24 | 21   | 17   |    |    |    |     |     |
|          |                 |             | 下方投影面積   | cm <sup>2</sup> | 1.25 | 47   | 40            | 35 | 31 | 44   | 38   | 33 | 29 | 39 | 34   | 30   | 27 | 34 | 30 | 27   | 24   | 20 |    |    |     |     |
| 等価発光面積   | cm <sup>2</sup> | 1.5         | 50       |                 | 43   | 38   | 34            | 47 | 41 | 36   | 33   | 41 | 37 | 33 | 30   | 36   | 33 | 30 | 27 | 22   |      |    |    |    |     |     |
| 取付<br>高さ |                 | 器具間隔最大限     |          | 2.0             | 53   | 48   | 43            | 40 | 50 | 45   | 41   | 38 | 45 | 41 | 37   | 35   | 39 | 36 | 34 | 31   | 26   |    |    |    |     |     |
|          |                 |             |          | 2.5             | 56   | 51   | 47            | 43 | 53 | 48   | 45   | 41 | 47 | 43 | 40   | 38   | 41 | 39 | 36 | 34   | 28   |    |    |    |     |     |
|          |                 | 横方向 ( A )   |          | 縦方向 ( B )       |      | 3.0  | 57            | 53 | 49 | 46   | 54   | 50 | 47 | 44 | 48   | 45   | 43 | 40 | 43 | 40   | 38   | 36 | 30 |    |     |     |
|          |                 |             |          |                 |      | 4.0  | 60            | 56 | 53 | 50   | 56   | 53 | 50 | 48 | 50   | 48   | 46 | 44 | 45 | 43   | 41   | 39 | 33 |    |     |     |
| H m      |                 | 1.62 H m    | 1.62 H m | 5.0             | 61   | 58   | 55            | 53 | 58 | 55   | 53   | 50 | 52 | 50 | 48   | 46   | 46 | 44 | 43 | 41   | 34   |    |    |    |     |     |
|          |                 |             |          | 7.0             | 63   | 60   | 58            | 56 | 60 | 57   | 55   | 54 | 53 | 52 | 50   | 49   | 48 | 46 | 45 | 44   | 37   |    |    |    |     |     |
|          |                 |             |          | 10.0            | 64   | 62   | 61            | 59 | 61 | 59   | 58   | 56 | 55 | 54 | 52   | 51   | 49 | 48 | 47 | 46   | 39   |    |    |    |     |     |

