

屋内照明器具特性	
品番 (品名)	L G B 1 5 3 8 0 K
光源	LDA13L - G / Z100E / S / W ×1 1520.0 l m
管理番号	K0138006 (0) DB 1
B Z 分類	BZ5 / 1.1 / BZ6

器具効率		95 %	反射率	天井	80 %				70 %				50 %				30 %				0 %		
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %		
				床	10 %				10 %				10 %				10 %				0 %		
上方光束		36 %	室指数	照明率 (X0.01)																	Z	C	M
下方光束		59 %																					
保守率		良 中 否	0.67	0.6	49	38	31	26	46	36	29	25	40	32	27	23	35	28	24	21	17		
			0.63	0.8	56	46	38	33	53	43	37	32	46	38	33	29	40	34	29	26	21		
			1.0	62	51	44	39	58	49	42	37	50	43	38	33	44	38	34	30	24			
			0.56	1.25	67	57	50	44	62	54	47	42	54	48	42	38	47	42	38	34	27		
下方投影面積		c m ²	1.5	70	61	54	49	66	58	52	47	57	51	46	42	50	45	41	37	30			
等価発光面積			c m ²	2.0	75	67	61	56	70	63	58	53	61	56	52	48	53	49	46	42	34		
取付 高さ	器具間隔最大限		2.5	78	71	66	61	73	67	62	58	64	59	55	52	56	52	49	46	37			
	横方向 (A)		縦方向 (B)	3.0	80	74	69	65	76	70	65	61	66	62	58	55	58	54	51	49	39		
H m	1.36 H m	1.37 H m	4.0	83	78	74	70	78	74	70	66	69	65	62	59	60	57	55	53	42			
			5.0	85	81	77	74	80	76	73	70	71	68	65	62	62	59	57	55	44			
			7.0	88	84	81	78	83	80	77	74	73	71	68	66	64	62	60	59	47			
			10.0	89	87	84	82	84	82	80	78	75	73	71	70	66	64	63	62	50			

