

屋内照明器具特性	
品番 (品名)	L G B 1 1 0 5 8 B
光源	LED2700_70_460 ×1 460.0 l m
管理番号	K0161574 (0) DB 1
B Z 分類	BZ8 / 0.7 / BZ7

器具効率		1 0 1 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
上方光束		3 8 %	室指数	照明率 (X 0 . 0 1)																	Z C M
下方光束		6 3 %																			
保守率		良 中 否	0 . 6 3	0 . 6	4 7	3 4	2 6	2 0	4 3	3 2	2 4	1 9	3 7	2 8	2 1	1 7	3 2	2 4	1 9	1 5	1 0
			0 . 6	0 . 8	5 5	4 3	3 4	2 8	5 1	4 0	3 2	2 6	4 4	3 5	2 8	2 3	3 7	3 0	2 5	2 0	1 5
				1 . 0	6 1	4 9	4 1	3 4	5 7	4 6	3 8	3 2	4 9	4 0	3 4	2 8	4 2	3 5	2 9	2 5	1 8
			0 . 5 6	1 . 2 5	6 7	5 6	4 7	4 0	6 2	5 2	4 4	3 8	5 4	4 5	3 9	3 4	4 6	3 9	3 4	3 0	2 2
下方投影面積		c m ²		1 . 5	7 1	6 0	5 2	4 6	6 6	5 7	4 9	4 3	5 7	4 9	4 3	3 8	4 9	4 3	3 8	3 3	2 5
			等価発光面積	c m ²	2 . 0	7 7	6 8	6 0	5 4	7 2	6 3	5 6	5 1	6 2	5 5	5 0	4 5	5 3	4 8	4 3	3 9
取付 高さ	器具間隔最大限			2 . 5	8 1	7 2	6 5	5 9	7 5	6 8	6 2	5 6	6 5	5 9	5 4	5 0	5 6	5 2	4 7	4 4	3 4
	横方向 (A) 縦方向 (B)			3 . 0	8 3	7 6	7 0	6 4	7 8	7 1	6 6	6 1	6 8	6 3	5 8	5 4	5 8	5 4	5 1	4 7	3 7
H m	1 . 4 9 H m	1 . 4 9 H m		4 . 0	8 7	8 1	7 5	7 0	8 2	7 6	7 1	6 7	7 1	6 7	6 3	5 9	6 2	5 8	5 5	5 2	4 1
				5 . 0	8 9	8 4	7 9	7 5	8 4	7 9	7 5	7 1	7 4	7 0	6 6	6 3	6 4	6 1	5 8	5 5	4 4
				7 . 0	9 2	8 8	8 4	8 0	8 7	8 3	7 9	7 6	7 6	7 3	7 0	6 8	6 7	6 4	6 2	6 0	4 7
				1 0 . 0	9 4	9 1	8 8	8 5	8 9	8 6	8 3	8 1	7 9	7 6	7 4	7 2	6 9	6 7	6 5	6 3	5 1

