

屋内照明器具特性	
品番 (品名)	LGB51569W
光源	LED3500_70_470 ×1 470.0 lm
管理番号	K0161574 (0) DB1
BZ分類	BZ8/0.7/BZ7

器具効率		101 %	反射率	天井	80 %				70 %				50 %				30 %				0 %					
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %					
				床	10 %				10 %				10 %				10 %				0 %					
上方光束		38 %	室指数	照明率 (X0.01)																			Z	C		M
下方光束		63 %																								
保守率		良 中 否	0.63	0.6	47	34	26	20	43	32	24	19	37	28	21	17	32	24	19	15	10					
			0.6	0.8	55	43	34	28	51	40	32	26	44	35	28	23	37	30	25	20	15					
				1.0	61	49	41	34	57	46	38	32	49	40	34	28	42	35	29	25	18					
			0.56	1.25	67	56	47	40	62	52	44	38	54	45	39	34	46	39	34	30	22					
下方投影面積		cm ²		1.5	71	60	52	46	66	57	49	43	57	49	43	38	49	43	38	33	25					
等価発光面積			cm ²	2.0	77	68	60	54	72	63	56	51	62	55	50	45	53	48	43	39	30					
取付 高さ	器具間隔最大限			2.5	81	72	65	59	75	68	62	56	65	59	54	50	56	52	47	44	34					
	横方向 (A)		縦方向 (B)	3.0	83	76	70	64	78	71	66	61	68	63	58	54	58	54	51	47	37					
H m	1.49 H m		1.49 H m	4.0	87	81	75	70	82	76	71	67	71	67	63	59	62	58	55	52	41					
				5.0	89	84	79	75	84	79	75	71	74	70	66	63	64	61	58	55	44					
				7.0	92	88	84	80	87	83	79	76	76	73	70	68	67	64	62	60	47					
				10.0	94	91	88	85	89	86	83	81	79	76	74	72	69	67	65	63	51					

