

屋内照明器具特性	
品番 (品名)	LGB54369B
光源	LED3500_70_470 ×1 470.0 lm
管理番号	K0161574 (0) DB1
BZ分類	BZ8/0.7/BZ7

器具効率		101 % 上方光束 38 % 下方光束 63 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
				床	10 %				10 %				10 %				10 %				0 %	
			室指数	照明率 (X0.01) ZCM																		
保守率		良 中 否	0.63	0.6	47	34	26	20	43	32	24	19	37	28	21	17	32	24	19	15	10	
			0.6	0.8	55	43	34	28	51	40	32	26	44	35	28	23	37	30	25	20	15	
			0.56	1.0	61	49	41	34	57	46	38	32	49	40	34	28	42	35	29	25	18	
				1.25	67	56	47	40	62	52	44	38	54	45	39	34	46	39	34	30	22	
下方投影面積		cm ²		1.5	71	60	52	46	66	57	49	43	57	49	43	38	49	43	38	33	25	
等価発光面積			cm ²	2.0	77	68	60	54	72	63	56	51	62	55	50	45	53	48	43	39	30	
				2.5	81	72	65	59	75	68	62	56	65	59	54	50	56	52	47	44	34	
取付	器具間隔最大限			3.0	83	76	70	64	78	71	66	61	68	63	58	54	58	54	51	47	37	
高さ	横方向 (A)		縦方向 (B)	4.0	87	81	75	70	82	76	71	67	71	67	63	59	62	58	55	52	41	
H m	1.49 H m		1.49 H m	5.0	89	84	79	75	84	79	75	71	74	70	66	63	64	61	58	55	44	
				7.0	92	88	84	80	87	83	79	76	76	73	70	68	67	64	62	60	47	
				10.0	94	91	88	85	89	86	83	81	79	76	74	72	69	67	65	63	51	

