

屋内照明器具特性	
品番 (品名)	L G B 8 1 4 6 8 W
光源	LED2700_70_460 ×1 460.0 l m
管理番号	K0161574 (0) DB 1
B Z 分類	BZ8 / 0.7 / BZ7

器具効率		101 % 上方光束 38 % 下方光束 63 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
			室指数	照明率 (X0.01) Z C M																	
保守率		良 中 否	0.63	0.6	47	34	26	20	43	32	24	19	37	28	21	17	32	24	19	15	10
			0.6	0.8	55	43	34	28	51	40	32	26	44	35	28	23	37	30	25	20	15
			0.56	1.0	61	49	41	34	57	46	38	32	49	40	34	28	42	35	29	25	18
				1.25	67	56	47	40	62	52	44	38	54	45	39	34	46	39	34	30	22
下方投影面積		c m ² 等価発光面積 c m ²		1.5	71	60	52	46	66	57	49	43	57	49	43	38	49	43	38	33	25
			2.0	77	68	60	54	72	63	56	51	62	55	50	45	53	48	43	39	30	
			2.5	81	72	65	59	75	68	62	56	65	59	54	50	56	52	47	44	34	
取付 高さ	器具間隔最大限			3.0	83	76	70	64	78	71	66	61	68	63	58	54	58	54	51	47	37
	横方向 (A)																				
H m	1.49 H m		1.49 H m	4.0	87	81	75	70	82	76	71	67	71	67	63	59	62	58	55	52	41
				5.0	89	84	79	75	84	79	75	71	74	70	66	63	64	61	58	55	44
				7.0	92	88	84	80	87	83	79	76	76	73	70	68	67	64	62	60	47
				10.0	94	91	88	85	89	86	83	81	79	76	74	72	69	67	65	63	51

