

# 屋内照明器具特性

|         |                     |             |
|---------|---------------------|-------------|
| 品番 (品名) | XLX830KHVJ          |             |
| 光源      | LED3500_85_12240 ×1 | 12240.0 1 m |
| 管理番号    | K0130921 (7) DB 1   |             |
| BZ分類    | BZ5                 |             |

|        |                  |         |                  |      |      |      |      |      |      |      |      |      |     |      |      |     |     |      |     |     |     |
|--------|------------------|---------|------------------|------|------|------|------|------|------|------|------|------|-----|------|------|-----|-----|------|-----|-----|-----|
| 器具効率   | 100 %            | 天井      | 80 %             |      |      |      | 70 % |      |      |      | 50 % |      |     |      | 30 % |     |     |      | 0 % |     |     |
|        | 上方光束             |         | 0 %              | 壁    | 70   | 50   | 30   | 10   | 70   | 50   | 30   | 10   | 70  | 50   | 30   | 10  | 70  | 50   | 30  | 10  | 0 % |
|        | 下方光束             |         | 100 %            |      | 床    | 10 % |      |      |      | 10 % |      |      |     | 10 % |      |     |     | 10 % |     |     |     |
| 室指数    | 照明率 ( X0.01 )    |         |                  |      |      |      |      |      |      |      |      |      |     |      |      |     |     |      |     |     | ZCM |
| 保守率    | 良                | 0.81    | 0.6              | 5.6  | 4.4  | 3.6  | 3.1  | 5.5  | 4.3  | 3.6  | 3.0  | 5.2  | 4.2 | 3.5  | 3.0  | 5.0 | 4.1 | 3.5  | 3.0 | 2.8 |     |
|        | 中                | 0.77    | 0.8              | 6.6  | 5.5  | 4.7  | 4.1  | 6.5  | 5.4  | 4.6  | 4.1  | 6.2  | 5.2 | 4.6  | 4.1  | 5.9 | 5.1 | 4.5  | 4.0 | 3.8 |     |
|        | 否                | 0.68    | 1.0              | 7.3  | 6.2  | 5.4  | 4.8  | 7.1  | 6.1  | 5.4  | 4.8  | 6.8  | 6.0 | 5.3  | 4.8  | 6.6 | 5.8 | 5.2  | 4.8 | 4.5 |     |
|        |                  |         | 1.25             | 7.9  | 6.9  | 6.2  | 5.6  | 7.7  | 6.8  | 6.1  | 5.6  | 7.4  | 6.6 | 6.0  | 5.5  | 7.1 | 6.5 | 5.9  | 5.5 | 5.3 |     |
| 下方投影面積 | c m <sup>2</sup> |         | 1.5              | 8.3  | 7.4  | 6.7  | 6.2  | 8.1  | 7.3  | 6.7  | 6.1  | 7.8  | 7.1 | 6.6  | 6.1  | 7.6 | 6.9 | 6.5  | 6.0 | 5.8 |     |
|        | 等価発光面積           |         | c m <sup>2</sup> | 2.0  | 8.9  | 8.1  | 7.5  | 7.0  | 8.7  | 8.0  | 7.5  | 7.0  | 8.4 | 7.8  | 7.3  | 6.9 | 8.1 | 7.6  | 7.2 | 6.8 | 6.6 |
| 取付高さ   | 器具間隔最大限          |         | 2.5              | 9.2  | 8.6  | 8.1  | 7.6  | 9.1  | 8.5  | 8.0  | 7.6  | 8.8  | 8.3 | 7.9  | 7.5  | 8.5 | 8.1 | 7.7  | 7.4 | 7.1 |     |
|        | 横方向 (A)          | 縦方向 (B) | 3.0              | 9.5  | 8.9  | 8.5  | 8.1  | 9.3  | 8.8  | 8.4  | 8.0  | 9.0  | 8.6 | 8.2  | 7.9  | 8.8 | 8.4 | 8.1  | 7.8 | 7.5 |     |
| 1.5m   | 2.06 m           | 2.87 m  | 4.0              | 9.8  | 9.4  | 9.0  | 8.7  | 9.7  | 9.3  | 8.9  | 8.6  | 9.4  | 9.0 | 8.7  | 8.5  | 9.1 | 8.8 | 8.6  | 8.3 | 8.1 |     |
| 2      | 2.69             | 3.3     | 5.0              | 10.0 | 9.7  | 9.3  | 9.0  | 9.9  | 9.5  | 9.2  | 9.0  | 9.6  | 9.3 | 9.1  | 8.8  | 9.3 | 9.1 | 8.9  | 8.7 | 8.4 |     |
| 2.5    | 3.31             | 3.79    | 7.0              | 10.2 | 10.0 | 9.7  | 9.5  | 10.1 | 9.8  | 9.6  | 9.4  | 9.8  | 9.6 | 9.4  | 9.2  | 9.6 | 9.4 | 9.2  | 9.1 | 8.8 |     |
| 3      | 3.94             | 4.33    | 10.0             | 10.4 | 10.2 | 10.0 | 9.9  | 10.3 | 10.1 | 9.9  | 9.8  | 10.0 | 9.9 | 9.7  | 9.6  | 9.8 | 9.6 | 9.5  | 9.4 | 9.1 |     |

