

屋内照明器具特性

品番 (品名)	L G W J 5 6 9 7 5 Z																
光源	LDA5 L - G / K40E / S / W ×1 485.0 l m																
管理番号	K0134339 (0) DR 1																
B Z 分類	BZ10																

器具効率	68 %	天井	80 %				70 %				50 %				30 %				0 %	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
上方光束	44 %	反射率	10 %				10 %				10 %				10 %				0 %	
下方光束	24 %		床	10 %				10 %				10 %				10 %				0 %
室指数			照明率 (X0.01) Z C M																	
保守率	良	0.63	0.6	2.9	2.1	1.6	1.2	2.6	1.9	1.4	1.1	2.0	1.5	1.1	8	1.5	1.1	8	6	2
	中	0.6	0.8	3.5	2.7	2.1	1.7	3.1	2.4	1.9	1.5	2.4	1.9	1.5	1.2	1.8	1.4	1.1	8	3
	否	0.56	1.0	3.9	3.1	2.5	2.1	3.4	2.8	2.3	1.9	2.7	2.2	1.8	1.5	2.0	1.6	1.3	1.1	4
			1.25	4.2	3.5	2.9	2.5	3.8	3.1	2.6	2.2	2.9	2.4	2.1	1.8	2.1	1.8	1.5	1.3	5
下方投影面積		cm ²	1.5	4.5	3.8	3.3	2.8	4.0	3.4	2.9	2.6	3.1	2.7	2.3	2.0	2.3	2.0	1.7	1.5	6
等価発光面積		cm ²	2.0	4.9	4.3	3.8	3.3	4.4	3.8	3.4	3.0	3.4	3.0	2.7	2.4	2.5	2.2	2.0	1.8	8
取付高さ	器具間隔最大限		2.5	5.1	4.6	4.1	3.7	4.6	4.1	3.7	3.4	3.6	3.3	3.0	2.7	2.7	2.4	2.2	2.0	1.0
	横方向 (A)	縦方向 (B)	3.0	5.3	4.8	4.4	4.0	4.8	4.3	4.0	3.6	3.8	3.4	3.2	2.9	2.8	2.6	2.4	2.2	1.1
H m	0.00 H m	0.00 H m	4.0	5.5	5.1	4.8	4.4	5.0	4.6	4.3	4.0	4.0	3.7	3.4	3.2	3.0	2.8	2.6	2.4	1.3
			5.0	5.7	5.3	5.0	4.7	5.1	4.8	4.5	4.3	4.1	3.9	3.6	3.4	3.1	2.9	2.8	2.6	1.4
			7.0	5.8	5.6	5.3	5.1	5.3	5.1	4.8	4.6	4.2	4.1	3.9	3.7	3.3	3.1	3.0	2.9	1.6
			10.0	6.0	5.8	5.6	5.4	5.4	5.3	5.1	4.9	4.4	4.2	4.1	4.0	3.4	3.3	3.2	3.1	1.7

