

屋内照明器具特性

品番 (品名)	LGBC81033									
光源	LED2700_70_1410 x1 1410.0 lm									
管理番号	K0147588(0)DB1									
BZ分類	BZ6/0.7/BZ5/3.5/BZ6									

器具効率	100%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	9%	反射率	床	10%				10%				10%				10%				0%
下方光束	91%		室指数	照明率 (X0.01)																ZCM
保守率	良 中 否 0.63 0.6 0.56	0.6	53	41	33	27	52	40	32	27	48	38	31	26	45	36	30	26	23	
		0.8	63	51	42	36	61	50	42	36	57	47	40	35	53	45	39	34	31	
		1.0	69	58	50	43	67	56	49	43	63	54	47	42	59	51	45	41	37	
		1.25	75	64	57	50	73	63	55	50	68	60	53	48	64	57	52	47	43	
下方投影面積	c m ²	1.5	79	69	62	56	77	68	61	55	72	64	58	53	68	61	56	52	48	
		2.0	85	76	70	64	82	75	68	63	77	71	66	61	73	68	63	59	55	
取付高さ	器具間隔最大限		2.5	88	81	75	70	86	79	73	68	81	75	71	66	77	72	68	64	60
	横方向 (A)	縦方向 (B)	3.0	91	84	79	74	88	82	77	73	84	79	74	70	79	75	71	68	63
H m	1.29 H m	1.29 H m	4.0	94	89	84	80	92	87	83	79	87	83	79	76	83	79	76	73	68
			5.0	96	92	88	84	94	90	86	83	89	86	83	80	85	82	79	77	72
			7.0	99	95	92	89	96	93	90	87	92	89	87	84	88	85	83	81	76
			10.0	101	98	96	93	98	96	94	92	94	92	90	88	90	88	86	85	80

